



Mobil Delvac™ Super 1400 15W-40

Mobil Commercial Vehicle Lube , Indonesia

High Performance Diesel Engine Oil

Product Description

Mobil Delvac™ Super 1400 15W-40 is a high performance diesel engine oil that provides proven protection of diesel engines operating on and off- highway service applications. Mobil Delvac Super 1400 15W-40 is biodiesel compatible\* and is recommended by ExxonMobil for use in a wide range of heavy-duty applic and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Footnotes:

\*based on CEC L-109-14 (test modified with palm B100), meeting the limits in ACEA E7-16

Features and Benefits

The technology in Mobil Delvac Super 1400 15W-40 delivers excellent performance in both modern diesel engines as well as older models. The key benefits include:

| Features                         | Advantages and Potential Benefits           |
|----------------------------------|---|
| Thermal and oxidation stability  | Controls sludge build-up and deposits       |
| TBN reserve                      | Deposit control                             |
| Stay-in-grade shear stability    | Reduced oil consumption and wear protection |
| Excellent detergency/dispersancy | Cleaner engines and longer engine life      |
| Component compatibility          | Longer gasket and seal life                 |

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment of European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

| This product has the following approvals:                      |
|--|
| MB-Approval 228.3  |
| This product is recommended for use in applications requiring: |
| MAN M 3275-1   |
| ACEA E3  |

**This product is recommended for use in applications requiring:**

API CF

API CF-4

API CG-4

API SJ

Mack EO-M

VOLVO VDS-2

**Properties and Specifications**

| Property   |            |
|--|------------|
| Grade  | SAE 15W-40 |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 14.7       |
| Density @ 15.6 C, g/ml, ASTM D4052                         | 0.880      |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 108        |
| Ash, Sulfated, mass%, ASTM D874                            | 1          |
| Flash Point, °C, ASTM D92                                  | 227        |
| Viscosity Index, ASTM D2270                                | 140        |
| Total Base Number, mgKOH/g, ASTM D2896                     | 9          |
| Pour Point, °C, ASTM D97                                   | -27        |

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

ExxonMobil Asia Pacific Pte Ltd

Jakarta Representative Office

Wisma GKBI 27th Floor

Jl. Jenderal Sudirman No. 28

Jakarta 10210

Indonesia

+62 21 574 0707

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil





© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved