



Mobil Super™ 2000 X2 10W-40

Mobil Passenger Vehicle Lube , Indonesia

Premium Synthetic Technology Passenger Vehicle Engine Oil

Product Description

Mobil Super 2000 X2 10W-40 is an enhanced-premium synthetic technology engine oil, designed to provide an excellent level of protection for vehicles in city driving.

Features and Benefits

Mobil Super 2000 X2 10W-40 is industry proven so you can be assured that your vehicle is well protected from city driving conditions.

Mobil Super 2000 X2 10W-40 provides:

- Excellent wear protection
- Excellent engine cleanliness
- Excellent high temperature protection

Applications

Mobil Super 2000 X2 10W-40 is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Stop and Go City Driving
- Latest engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal to occasionally severe operating conditions
- Turbo-Chargers
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:

MB-Approval 229.1

VW 501 01

VW 505 00

This product is recommended for use in applications requiring:

This product is recommended for use in applications requiring:

API CF

This product meets or exceeds the requirements of:

API SJ

API SL

API SM

API SN

API SN PLUS

ACEA A3/B3

Properties and Specifications

Property	
Grade	SAE 10W-40
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	95
Viscosity Index, ASTM D2270	155
Density @ 15.6 C, g/ml, ASTM D4052	0.867
Pour Point, °C, ASTM D97	-42
Flash Point, Cleveland Open Cup, °C, ASTM D92	234
Ash, Sulfated, mass%, ASTM D874	0.9
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.8

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2021

ExxonMobil Asia Pacific Pte Ltd

Jakarta Representative Office

Wisma GKBI 27th Floor

Jl. Jenderal Sudirman No. 28

Jakarta 10210

Indonesia

+62 21 574 0707



<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved