



## Mobil 1™ FS x2 5W40

Mobil Passenger Vehicle Lube , Indonesia

Advanced Performance Synthetic Lubricant

### Product Description

Mobil 1™ FS x2 5W-40 is an advanced high performance synthetic engine oil designed to help provide outstanding wear protection, excellent cleaning power and outstanding overall performance. Mobil 1 FS x2 5W-40 meets or exceeds the requirements of many of the industry and OEM specifications required by newer gasoline and diesel powered automobile engines. Mobil 1 technology is race proven and is chosen by many racecar drivers around the world. Mobil 1 FS x2 5W-40 is perfect for all types of driving and has the performance to protect when conventional engine oils often may not.

### Features and Benefits

Mobil 1 FS x2 5W-40 is made with a proprietary blend of ultra-high performance synthetic basestocks fortified with a precisely balanced component system. Mobil 1 FS x2 5W-40 has been designed to help protect your engine by providing unsurpassed levels of performance during normal operating conditions and also under severe service such as extreme heat and cold. Key features and potential benefits include:

| Features                                    | Advantages and Potential Benefits   |
|---|---|
| Active cleaning agents                      | Helps to reduce deposits and sludge build-up to enable long and clean engine life   |
| Outstanding thermal and oxidative stability | Helps to resist oil aging allowing extended drain interval protection   |
| Low Oil Volatility                          | Less oil consumption  |
| Excellent low temperature capabilities      | Quick cold weather starting and fast protection.<br>Helps to extend engine life   |
| High Viscosity Index                        | Excellent overall lubrication and wear protection performance for all driving styles and conditions, from mild to severe. |

### Applications

Mobil 1 FS x2 5W-40 is recommended for all types of vehicles, including high-performance turbo-charged, supercharged gasoline and certain diesel multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks where the following specifications are required:

### Specifications and Approvals

| This product has the following approvals: |
|---|
| MB-Approval 229.3                         |
| Porsche A40                               |
| VW 502 00                                 |
| VW 505 00                                 |

**This product is recommended for use in applications requiring:**

API CF

**This product meets or exceeds the requirements of:**

ACEA A3/B3

ACEA A3/B4

API SN

API SM

API SL

API SJ

**Properties and Specifications**

| Property   |           |
|--|-----------|
| Grade  | SAE 5W-40 |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445                                      | 80        |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445                                     | 13.7      |
| Ash, Sulfated, mass%, ASTM D874  | 1.3       |
| Phosphorus, mass%, ASTM D4951  | 0.1       |
| Flash Point, Cleveland Open Cup, °C, ASTM D92  | 227       |
| Density @ 15 C, g/cm <sup>3</sup> , ASTM D4052   | 0.85      |
| Total Base Number, mgKOH/g, ASTM D2896   | 12.6      |
| Mini-Rotary Viscometer, Yield Stress, -35 C, Pa, ASTM D4684                                    | 17,000    |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 <sup>(6)</sup> sec <sup>(-1)</sup> , mPa.s, ASTM D4683 | 3.8       |

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2022

ExxonMobil Asia Pacific Pte Ltd

Jakarta Representative Office

Wisma GKBI 27th Floor

Jl. Jenderal Sudirman No. 28

Jakarta 10210

Indonesia

+62 21 574 0707

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved