



## Mobil Delvac 1 SHC 5W40

Mobil Commercial Vehicle Lube , Ireland

Very High Performance Diesel Engine Oil

### Product Description

Mobil Delvac 1 SHC 5W-40 is a very high performance, synthetic diesel engine oil that provides excellent lubrication including long drain capability, helping towards long engine life for diesel engines operating in severe applications. The advanced technology behind this product delivers exceptional performance in turbo-charged as well as older naturally aspirated engines. Mobil Delvac 1 SHC 5W-40 is recommended for use in a wide range of heavy-duty applications and operating environments found in trucking, mining, construction, agriculture and marine.

### Features and Benefits

Modern high output diesel engines run hotter than older engines which significantly increases the demands on engine lubricants. Current tighter engine designs reduce oil consumption, resulting in less fresh oil makeup to replenish depleted additives. Top piston rings are located higher bringing the oil film closer to the combustion chamber where temperatures increase thermal stress on the lubricant. Mobil Delvac 1 SHC 5W-40 helps to protect the engine under severe operating conditions. It is also fully compatible with conventional mineral oils. The key benefits include:

Features	Advantages and Potential Benefits
Excellent thermal and oxidation stability	Control of low temperature sludge build-up and high temperature varnish deposits
High TBN	Helps towards extended drain intervals with high sulphur fuels
Advanced formulation and viscometrics	Maintains viscosity in severe, high temperature service
Excellent low temperature pumpability	Easier engine start-up and reduced wear
Good resistance to corrosion	Helps towards long life of critical wear surfaces
Long drain capability	Helps towards good operating efficiency and lower overall cost
Component compatibility	Long gasket and seal life, extended service intervals
Low volatility, excellent wear and bore polishing control	Good oil consumption control

### Applications

- Mobil Delvac 1 SHC 5W-40 is recommended for use in super high performance diesel applications including turbo-charged and naturally aspirated engines designs
- These applications include: on-highway engines operating in both high speed/high load and short haul pick-up/delivery; off-highway and marine engines operating in severe low speed/heavy load conditions
- Diesel powered equipment from European builders

### Specifications and Approvals

<b>This product has the following approvals:</b>
MAN M 3277

**This product has the following approvals:**

MTU Oil Category 3

MB-Approval 228.5

**This product is recommended for use in applications requiring:**

API CE

API CF

VOLVO VDS-2

**Properties and Specifications**

Property	
Grade	SAE 5W-40
Ash, Sulfated, mass%, ASTM D874	1.9
Density @ 15 C, kg/l, ASTM D4052	0.859
Flash Point, Cleveland Open Cup, °C, ASTM D92	238
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.2
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	84
Pour Point, °C, ASTM D97	-45
Total Base Number, mgKOH/g, ASTM D2896	16
Viscosity Index, ASTM D2270	176

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved