



## Mobil Chassis Grease LBZ

Mobil Grease , Ireland

Automotive Grease

### Product Description

Mobil Chassis Grease LBZ is a semi-fluid grease based on synthetic oils in the consistency group NLGI 00-000. It was specifically developed for central lubrication systems for commercial vehicles. The product contains anti-oxidants, corrosion inhibitors, extreme pressure and anti-wear additives. Due to its special formulation and semi-fluid consistency, Mobil Chassis Grease LBZ exhibits excellent flow even at very low temperatures and in long pipelines. The oil film adheres well and does not run off, even during stoppages. There is rapid on-flow to the greasing points. The good protection against rust also covers the use of 'spreading' salt and the related danger of rust on the lubrication points of the chassis. Mobil Chassis Grease LBZ is compatible with seals made of NBR, ACM and FKM, as long as these are suitable for the operating temperatures.

### Features and Benefits

| Features   | Advantages and Potential Benefits  |
|--|--|
| Good pumpability in centralised systems even at low temperatures                         | Potential to rationalise onto one product  |
| Designed for centralised lubrication systems   | Reduced operating costs compared to greasing by hand due to lower maintenance costs and economic usage |
| Reduced wear under heavy or shock loading and vibration. Excellent anti-wear performance | Good equipment reliability and availability  |
| Good protection against rust and corrosion and resistance to water wash out              | Enhanced equipment protection and good lubrication even in presence of water                           |
| Controlled oil release   | Balanced lubrication properties for longer service life  |

### Applications

#### Recommended by ExxonMobil for use in:

Central lubrication systems using semi-fluid greases in commercial vehicles -50°C and 100°C

The semi-fluid grease systems of the following manufacturers:

- Willie Vogel AG, Berlin (to -25°C )
- Mercedes Benz (Sheet 264.0 Semi-Fluid Greases).

### Specifications and Approvals

| Mobil Chassis Grease LBZ has the following builder approvals |                    |
|--|--------------------|
| Mercedes Benz  | MB-Approval 264.0  |
| MAN  | MAN 283 Li-P 0-000 |

### Typical Properties

| Mobil Chassis Grease LBZ |  |
|--------------------------|--|
|                          |  |

|   |                         |
|---|-------------------------|
| <b>Mobil Chassis Grease LBZ</b>                 |                         |
| NLGI Grade                                      | 00-000                  |
| Base Oil Viscosity @ 40°C, cSt, DIN EN ISO 3104 | 42                      |
| Thickener Type                                  | Lithium                 |
| Colour  | Beige-Brown transparent |
| Penetration, Worked, 25 °C, ASTM D 217          | 435-445                 |
| Dropping Point, D 2265, C                       | >160                    |
| 4-Ball Weld Load, N, DIN 51350-4                | 2200                    |
| Flow Pressure Test @ -35°C, hPa, DIN 51805      | 50                      |
| Temperature range, continuous operation         | -40°C to +100°C         |

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil Chassis Grease LBZ are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

05-2020

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved