



Mobilcut Series

Mobil Industrial , Ireland

Aqueous Metal Working Fluids

Product Description

Mobilcut is the trademark for Mobil Industrial lubricants line of high performance water miscible metal removal fluids. Formulated with leading edge base oils, additives and emulsifiers, the Mobilcut series of non-chlorinated products provides dependable performance in a wide array of metal removal processes. The products are designed to work in a variety of hard and soft water qualities and offer low foam potential and long-term corrosion protection for machine and components maintenance and inherently stable, Mobilcut products are designed for the modern machine shop where long service life, excellent machining performance and environmental concerns are important factors for increased productivity. These products are supplied in concentrated form and require mixing with water prior to use.

Mobilcut 100 is a conventional milky soluble oil that readily mixes with different waters to form stable emulsions. Its versatile performance makes it suitable for a range of metal cutting and grinding operations for both ferrous and non ferrous materials where economical performance is the main consideration. It offers excellent emulsion stability and long-term corrosion protection for both components and machine tool.

Enhanced with lubricity agents, Mobilcut 140 is a long life water soluble fluid making it an ideal choice for moderate to heavy duty machining applications in the machine shop. It is formulated to provide long service life and good emulsion stability and durability while helping to increase tool life and surface finish, even in complex machining operations. Mobilcut 140 is an ideal choice where excellent machining performance is required for a wide variety of materials and applications while being easy to monitor and maintain.

Mobilcut 250 is a high performance semi-synthetic fluid formulated to enhance performance when machining aluminum and aluminum alloys and where low foam potential is important on sensitive components. Containing high levels of lubricity agents, it provides high machining performance of carbon and alloy steels and other metals.

Mobilcut 320 is an inherently stable, synthetic (mineral oil-free) metalworking fluid. It is designed for general grinding operations where a high quality surface finish, outstanding cooling and low foaming potential are the primary requirements. It will help maintain free and open grinding wheels for maximum performance and significant marked stability for long service life.

Features and Benefits

The Mobilcut series of products are designed to help increase the productivity of modern machine shops by providing high performance features

| Features | Advantages and Potential Benefits |
|--|--|
| Form stable emulsions and solutions | Ease of use and maintenance |
| Long term inherent stability | Increases batch life and reduces unpleasant odors |
| Low foaming potential | Improved performance even in high pressure systems |
| Resists formation of sticky residues | Improves machine cleanliness |
| High degree of corrosion protection | Reduces machine maintenance and rework of materials |
| Good separability from fines | Improves filterability and surface finish |
| Wide Range of applicability | Potential to consolidate products and reduce inventories |
| Compatible with high performance Mobil Vactra Oil No slideway lubricants | Easy separation and removal of tramp oil |
| Neutral Odor | Enhances the workplace environment |

Applications

Mobilcut 100: General machining of easy to machine steels and copper alloys in light to moderate duty machining operations such as milling, turning, sawing, turning, drilling and reaming.

Mobilcut 140: Machining of aluminum and high machinability steels in moderate to heavy duty operations such as milling, turning, sawing, boring, drilling and reaming where the lubricity of a soluble oil is desired.

Mobilcut 250: Semi synthetic cutting fluid primarily intended for the machining of aluminum and aluminum alloys. It may also be used on a wide variety of materials where a more versatile fluid is required.

Mobilcut 320: Synthetic (mineral oil-free) grinding fluid, primarily recommended for grinding of steels and cast iron.

Properties and Specifications

| Property | 100 | 140 | 250 | 320 |
|---|--------------|----------------|----------------|-------------------|
| Appearance, AA.Lab.101 | Brown Liquid | | | |
| Appearance, PTM 100 | | Yellow, Liquid | Brown Liquid | Colourless liquid |
| Appearance, 3.0% in 15 deg dH Water, AA.Lab.101 | | | | Clear |
| Appearance, 4.0% in 15 deg dH Water, AA.Lab.101 | | | | |
| Appearance, 5% in 15 deg dH Water, Visual, AA.Lab.101 | | Milky | | |
| Appearance, 7.0% in 15 deg dH Water, AA.Lab.101 | Milky | | | |
| Corrosion Test, 3.0% in 15 deg dH Water, DIN 51360-2 | | | | 3 |
| Corrosion Test, 4.0% in 15 deg dH Water, DIN 51360-2 | | | 4 | |
| Corrosion Test, 7.0% in 15 deg dH Water, DIN 51360-2 | 7 | | | |
| Emulsion Type @ 3% in 50 ppm water, Rating, PTM 141 | | | Semi-synthetic | Synthetic |
| Emulsion Type @ 5% in 50 ppm water, Rating, PTM 141 | | Soluble | | |
| Refractive Index, per deg Brix, %, AA.Lab.105 | 0.95 | 1.0 | 0.9 | 1.45 |
| pH at 5% in Distilled Water, PTM 104 | | 9.1 | | |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2021

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved