



Mobil Super™ 2T

Mobil Passenger Vehicle Lube , Ireland

High Performance Two-Stroke Engine Oil

Product Description

Mobil Super 2T is a high performance, two-stroke engine oil for use in motorcycles, snowmobiles and lean oil/fuel ratio chain saws. Mobil Super 2T is pre-diluted to ensure rapid mixing when added to fuel.

Features and Benefits

Mobil Super 2T combines quality mineral oils with a strong additive system to provide good overall cleaning and performance. Key features and benefits include:

| Features | Advantages and Potential Benefits |
|---|--|
| Good wear protection | Helps provide longer engine life |
| Thermal and oxidation stability and deposit control | Cleaner engines resulting in extended spark plug and valve life, reduced ring sticking and piston tightening as well as protection against pre-ignition problems |
| Good corrosion protection properties | Helps provide longer engine life |
| Reduces pre-ignition | Improved fuel efficiency and extended piston life |

Specifications and Approvals

| This product meets or exceeds the requirements of: |
|--|
| API TC |
| JASO FB |
| ISO-L-EGB |

Properties and Specifications

| Property | |
|--|-------|
| Ash, Sulfated, mass%, ASTM D874 | 0.05 |
| Density @ 15 C, kg/l, ASTM D4052 | 0.878 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 132 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 8.7 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 63 |
| Pour Point, °C, ASTM D97 | -12 |

| Property | |
|-----------------------------|-----|
| Viscosity Index, ASTM D2270 | 110 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX


44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved