



## Mobil Delvac XHP™ 15W-40

Mobil Commercial Vehicle Lube , Israel

High Performance Diesel Engine Oil

### Product Description

Mobil Delvac XHP™ 15W-40 is a high performance diesel engine oil that provides protection for diesel engines operating under severe service conditions for on and off-highway applications. Mobil Delvac XHP 15W-40 is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

### Features and Benefits

Thermal and oxidation stability Helps to control sludge build-up and deposits

TBN reserve Helps to control deposits

Stay-in-grade shear stability Helps to reduce oil consumption and to provide wear protection

Excellent detergency/ dispersancy Helps to protect and to maintain engines clean

Component compatibility Long gasket and seal life

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Helps to control sludge build-up and deposits
TBN reserve	Helps to control deposits
Stay-in-grade shear stability	Helps to reduce oil consumption and to provide wear protection
Excellent detergency/ dispersancy	Helps to protect and to maintain engines clean
Component compatibility	Long gasket and seal life

### Applications

- Naturally aspirated and turbo-charged diesel powered equipment of European, Japanese, and American manufacturers in line with owner manual recommendations
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

### Specifications and Approvals

This product has the following approvals:
MTU Oil Category 1

This product is recommended for use in applications requiring:
ACEA A2
ACEA B2
ACEA E3

**This product is recommended for use in applications requiring:**

API CF

API CF-4

API CG-4

RENAULT TRUCKS RLD

RENAULT TRUCKS RLD-2

VOLVO VDS-2

**This product meets or exceeds the requirements of the following industry specification:**

API SJ

**Properties and Specifications**


Property	
Grade	SAE 15W-40
Specific Gravity, 15 C/15 C, ASTM D4052	0.88
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	106
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.5
Ash, Sulfated, mass%, ASTM D874	1.1
Pour Point, °C, ASTM D97	-27
Viscosity Index, ASTM D2270	140
Cold-Cranking Simulator, Apparent Viscosity @ -20 C, mPa.s, ASTM D5293	6150
Total Base Number, mgKOH/g, ASTM D2896	10

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2024

**ExxonMobil**

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved