



Mobil Delvac Modern 15W-40 Super Defense

Mobil Commercial Vehicle Lube , India
Synthetic Technology Extra High Performance Diesel Engine Oil

Product Description

Mobil Delvac Modern 15W-40 Super Defense is an extra high performance diesel engine oil that provides excellent wear protection to modern diesel engines pror long engine life. This product meets or exceeds the specifications of major European, Japanese and American engine manufacturers.

This product provides outstanding performance in both modern, demanding low-emission diesel engines as well as older diesel engines. Mobil Delvac Modern 15W-40 Super Defense combines high performance base stocks with a progressive additive system to provide control of oil thickening and high temperature deposits to p excellent engine performance.

Features and Benefits

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Reduced sludge build-up, deposits and viscosity increase
TBN reserves	Deposit control and acid neutralisation
Stay-in-grade shear stability	Wear protection and viscosity control
High detergency/dispersancy	Clean engines and long component life
Improved soot handling	Improved viscosity control and used oil pumpability
Excellent low temperature properties	Start-up wear protection
Component compatibility	Long gasket and seal life
Meets demanding specifications of key OEMs	One engine oil for mixed fleet operations

Applications

- Recommended by ExxonMobil for use in:
- Naturally aspirated and turbo-charged diesel powered. equipment from leading Japanese, European, and American manufacturers.
 - On-highway light and heavy-duty trucking.
 - Off-highway industries including: construction, mining, quarrying, and agriculture.
 - Mixed fleet applications.

Specifications and Approvals

This product has the following approvals:
Detroit Fluids Specification 93K215
Mack EO-M Plus
Mack EO-N
MB-Approval 228.3

This product has the following approvals:
MTU Oil Category 2
RENAULT TRUCKS RLD-2
VOLVO VDS-3

This product is recommended for use in applications requiring:
RENAULT TRUCKS RLD
VOLVO VDS-2
API CF-4
API CG-4
Cummins CES 20072
MACK EO-M
Cummins CES 20071

This product meets or exceeds the requirements of:
API CH-4
API CI-4
API SJ
ACEA E7
API SL
Caterpillar ECF-2

Properties and Specifications

Property	
Grade	SAE 15W-40
Cold-Cranking Simulator, Apparent Viscosity @ -20 C, mPa.s, ASTM D5293	5800
Ash, Sulfated, mass%, ASTM D874	1.1
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Pour Point, °C, ASTM D97	-36
Total Base Number, mgKOH/g, ASTM D4739	9.2
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	110
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.6

Property	
Viscosity Index, ASTM D2270	136
Density @ 15 C, kg/m3, ASTM D4052	0.87

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2022

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,

Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect pro performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without nc All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intende override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved