



Mobil Delvac TM Genuine CF-4 Oil 15W-40

Mobil Commercial Vehicle Lube , India

Heavy Duty Engine Oils

Product Description

Mobil Delvac TM Genuine CF-4 Oil 15W-40 is a high performance, heavy duty engine oil that provides proven protection to diesel engines operating in severe on and off-highway service applications. Mobil Delvac TM Genuine CF-4 Oil 15W-40 is primarily intended for use in Tata Motors Diesel Commercial Vehicles.

Features and Benefits

The key benefits of Mobil Delvac TM Genuine CF-4 Oil 15W-40 include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Stay-in-grade shear stability	Helps reduce oil consumption and wear

Applications

It is designed as per requirement of Engine oil for use in BS I/ BS II Commercial vehicle diesel engines manufactured by Tata Motors.

Specifications and Approvals

Mobil Delvac TM Genuine CF-4 Oil 15W-40 is recommended by ExxonMobil for use in applications requiring		
API CF-4		X

Typical Properties

Mobil Delvac TM Genuine CF-4 Oil 15W-40	
SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	105
cSt @ 100°C	14.4
Viscosity Index, ASTM D 2270	140
Sulfated Ash, wt%, ASTM D 874	1.1
Total Base # , mg KOH/g, ASTM D 2896	8
Pour Point, °C, ASTM D 97	-30
Flash Point, °C, ASTM D 92	220
Density @ 15°C kg/l, ASTM D 4052	0.876

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2019

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,
Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All
Rights Reserved