



## Mobil Delvac Legend™ 20W-40 Tractor Oil

Mobil Commercial Vehicle Lube , India

High Performance Heavy Duty Tractor Lubricant

### Product Description

Mobil Delvac Legend™ 20W-40 Tractor Oil is a high performance, heavy duty Tractor Lubricant that provide excellent protection to Tractors & Other Agricultural Machines operating in severe on and off-highway service applications. The lubricant is designed to meet wide range of Tractor & Agri-Machinery applications under varied load conditions of farming as well as driving on the road.

### Features and Benefits

Mobil Delvac Legend™ 20W-40 Tractor Oil is designed to meet requirements of very high RPM & Temperature conditions inside Agricultural application & Engines.

Features	Advantages and Potential Benefits
Excellent sludge control	Keeps Engine clean from inside
Excellent Wear & corrosion protection	Reduces wear & tear of Engine, increases Engine life
Long lasting Detergency & dispersency	Keeps Engine Clean & maintains lubricant performance
Better Thermal & Oxidation Stability	Longer Engine life and longer Oil Drain period

### Applications

Tractor & Agricultural Machinery

Diesel-powered equipment from leading engine manufacturers.

It can also be used in Off highway industries including: trucking, construction, quarrying

### Specifications and Approvals

<b>This product is recommended for use in applications requiring:</b>
API CF-4

### Properties and Specifications

Property	
Grade	SAE 20W-40
Pour Point, °C, ASTM D97	-24
Flash Point, Cleveland Open Cup, °C, ASTM D92	233
Density @ 15 C, g/ml, ASTM D1298	0.879

Property	
Total Base Number, mgKOH/g, ASTM D2896	6
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.6
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	123
Ash, Sulfated, mass%, ASTM D874	0.08

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2021

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,  
Whitefield Main Road, Bangalore – 560048, Karnataka, India


+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved