



Mobil Delvac Modern™ 15W-40 Super Fleet

Mobil Commercial Vehicle Lube , India

Synthetic Technology Commercial Vehicle Engine Oil

Product Description

Mobil Delvac Modern™ 15W-40 Super Fleet is an extra high performance synthetic technology diesel engine oil that provides excellent lubrication to both on highway and off highway diesel engines. It offers upto 60%* more wear protection than API CI-4 PLUS standards thus reducing engine maintenance cost along with long oil drain interval.

* Based on Cummins M11 EGR/Cummins ISM engine test

Features and Benefits

Mobil Delvac Modern 15W-40 Super Fleet is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance. The key benefits include:

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Reduced sludge build-up and deposits resulting long oil and filter life
Improved soot handling	Exceptional viscosity control and better engine performance
Advanced detergency/dispersancy	Clean engines and long component life
TBN reserves	Deposit control and acid neutralisation resulting long component life
Exceptional wear protection	Long component life and reduced maintenance cost

Applications

Ideal for use in BS II, BS III, BS IV (without DPF), Euro II and Euro III compliant turbo charged commercial vehicles diesel engines.

Specifications and Approvals

This product has the following approvals:
VOLVO VDS-3

This product meets or exceeds the requirements of:
API CI-4 PLUS
CUMMINS CES 20078

Properties and Specifications

Property	

Property	
Grade	SAE 15W-40
Viscosity Index, ASTM D2270	137
Total Base Number, mgKOH/g, ASTM D2896	11
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	109
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.5
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Density @ 15 C, g/cm ³ , ASTM D1298	0.877
Ash, Sulfated, mass%, ASTM D874	1.4

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2021

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,

Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil ESSEO XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved