



Mobil Delvac Legend 15W-40 Tractor Oil

Mobil Commercial Vehicle Lube , India

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Legend 15W-40 Tractor Oil is Premium tractor engine oil that provides protection to modern turbo charged or naturally aspirated tractor engines operating on and off-highway service applications. It is recommended by ExxonMobil for use in modern tractor engines and can also be used in stationary engines (DG sets), construction and other agricultural implements.

Features and Benefits

Mobil Delvac Legend 15W-40 Tractor Oil is Multigrade diesel engine oil for excellent performance in both modern as well as older tractors and other agri-machineries equipped with turbo & non-turbo diesel engines. The key benefits include:

Features	Advantages and Potential Benefits
Stay-in-grade shear stability	Reduced Oil consumption & better wear protection
TBN reserve	Controls Deposit and helps acid neutralisation during tough tractor in-field applications
Excellent detergency/dispersancy	Clean engines and long engine life
Thermal and oxidation stability	Controls sludge and deposits, thereby keeping internal engine parts clean

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered Tractor engines & Agriculture equipment
- On-highway medium and heavy duty trucking
- Off-highway industries including: construction, mining, quarrying, stationary engine applications including agriculture implements

Specifications and Approvals

This product meets or exceeds the requirements of:
API CH-4

Properties and Specifications

Property	
Grade	SAE 15W-40

Property	
Viscosity Index, ASTM D2270	137
Ash, Sulfated, mass%, ASTM D874	1.1
Density @ 15 C, kg/l, ASTM D4052	0.869
Flash Point, Cleveland Open Cup, °C, ASTM D92	233
Pour Point, °C, ASTM D97	-33
Total Base Number, mgKOH/g, ASTM D2896	8
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	15.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	116

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

ExxonMobil Services & Technology Private Limited
(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,
Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved