



Mobil Super™ Everyday Protection 10W-30

Mobil Passenger Vehicle Lube , India

Everyday Protection Premium Mineral Engine Oil

Product Description

Mobil Super™ Everyday Protection is a premium mineral engine oil that delivers proven protection to extend engine life.

Formulated with the ExtEngine™molecule, an age-defying, anti-wear ingredient, Mobil Super™ Everyday Protection reacts to engine-damaging stress by cre: long-lasting protective barrier for better wear protection.

Mobil Super™ Everyday Protection meets the requirements of modern gasoline vehicle engines. Suitable for Indian, Japanese and Korean cars including Tata, 1 Honda, Nissan, Suzuki, Mitsubishi, Hyundai, and more.

Features and Benefits

- Premium mineral engine oil for everyday protection
- ExtEngine molecules for a long-lasting protective barrier to extend engine life
- Reduce wear and tear, thereby reducing maintenance costs
- Good high and low temperature protection performance under severe driving conditions

Applications

ExxonMobil recommends Mobil Super™ Everyday Protection for daily driving under normal conditions:

- Gasoline engine technologies
- Passenger cars, SUVs, light trucks and vans

Always consult your owner's manual to check the recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:	
API SL	
API SN Engine Test Requirements	

Properties and Specifications

Property	
Grade	SAE 10W-30
Pour Point, °C, ASTM D97	-36
Density @ 15 C, g/ml, ASTM D4052	0.869

Property	
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	15200
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.3
Viscosity Index, ASTM D2270	136
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	69
Flash Point, Cleveland Open Cup, °C, ASTM D92	243
Ash, Sulfated, mass%, ASTM D874	0.9
Total Base Number, mgKOH/g, ASTM D2896	7.6
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.2

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2023
ExxonMobil Services & Technology Private Limited
(CIN: U74900KA2015FTC080245)
Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,
Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved