



Mobil Super™ 3000 Formula I 5W-40
Mobil Passenger Vehicle Lube , India
Premium Fully Synthetic Passenger Vehicle Engine Oil

Product Description

The Mobil Super™ 3000 Formula I 5W-40 is an ultra premium synthetic engine oil, designed to provide outstanding levels of protection and performance.

Features and Benefits

Mobil Super 3000 Formula I 5W-40 is industry proven so you can trust you will get the performance you want from your vehicle.

Mobil Super 3000 Formula I 5W-40 provides:

- Outstanding wear protection
- Outstanding engine cleanliness
- Outstanding high temperature protection
- Outstanding low temperature protection

Applications

Mobil Super 3000 Formula I 5W-40 is formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. We particularly recommend Mobil Super 3000 Formula I 5W-40 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV’s, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions
- Turbo-Chargers and Direct Injection engines
- High Performance Engines

Always consult your owner’s manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

Mobil Super 3000 Formula I 5W-40 meets or exceeds the requirements of:	
API	SM/SL/SJ

Mobil Super Formula I 5W-40 is recommended by ExxonMobil for use in applications requiring:	
FIAT	9.55535-N2
API	CF

Typical Properties

Mobil Super 3000 Formula I 5W-40	
SAE Grade	5W-40
Viscosity, ASTM D 445	

Mobil Super 3000 Formula I 5W-40	
cSt @ 40° C	83
cSt @ 100°C	14.0
Viscosity Index, ASTM D 2270	174
Sulfated Ash, wt%, ASTM D 874	1.0
HTHS Viscosity, mPa•s @ 150° C, ASTM D4683	3.7
Pour Point, °C, ASTM D 97	-42
Flash Point, °C, ASTM D 92	232
Density @15° C kg/l, ASTM D 4052	0.860

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2019
ExxonMobil Services & Technology Private Limited
(CIN: U74900KA2015FTC080245)
Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,
Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTON

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved