



## Mobil Super™ 1000 Diesel 15W-40

Mobil Passenger Vehicle Lube , India

### Product Description

The Mobil Super™ 1000 range of lubricants are premium mineral engine oils, designed to provide a high level of protection and performance.

### Features and Benefits

Mobil Super 1000 products are industry tested so you can trust you will get the performance you want from your vehicle.

Mobil Super 1000 provides:

Good high temperature protection

- Good wear protection
- Good engine cleanliness

### Applications

Mobil Super 1000 products have been formulated for use in many vehicles. Mobil Super 1000 Diesel 15W-40 is suitable for:

- Many Diesel engine technologies
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal Operating Conditions

We particularly recommend Mobil Super 1000 Diesel 15W-40 for daily driving under normal conditions. Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

**This product meets or exceeds the requirements of:**

API CH-4

### Properties and Specifications

Property	
Grade	SAE 15W-40
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	15.2
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	116
Viscosity Index, ASTM D2270	137
Ash, Sulfated, mass%, ASTM D874	1.1

Property	
Total Base Number, mgKOH/g, ASTM D2896	8.5
Pour Point, °C, ASTM D97	-33
Flash Point, Cleveland Open Cup, °C, ASTM D92	233
Density @ 15 C, kg/l, ASTM D4052	0.869

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,  
Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil Esso XTO

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved