



MOBIL SUPER EVERYDAY PROTECTION 20W-50

Mobil Passenger Vehicle Lube , India

High Performance Motor Oil

Product Description

Mobil Super™ Everyday Protection 20W-50 is brought to you by the makers of Mobil 1™. This premium multigrade engine oil is formulated with proprietary Extengine™ molecule to provide a high level of engine protection for long engine life.

Features and Benefits

- Proprietary Extengine™ molecule for long engine life.
- Improved engine protection.
- Helps keep engine clean.

Applications

- Suitable for Petrol, CNG and LPG engines.
- Suitable for old and new passenger cars, light trucks and vans.
- Normal to elevated operating conditions.

Specifications and Approvals

This product is recommended for use in applications requiring:
API SN
API SM

Properties and Specifications

Property	
Grade	SAE 20W-50
Pour Point, °C, ASTM D97	-30
Mini-Rotary Viscometer, Apparent Viscosity, -20 C, mPa.s, ASTM D4684	17400
Total Base Number, mgKOH/g, ASTM D2896	7.4
Ash, Sulfated, mass%, ASTM D874	0.9
Flash Point, Cleveland Open Cup, °C, ASTM D92	240
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	162.9

Property	
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	4.8
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	18
Viscosity Index, ASTM D2270	122

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,
Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved