



## Mobil Super™ 1000 TM 15W-40

Mobil Passenger Vehicle Lube , India

Premium Multigrade Passenger Vehicle Engine Oil

### Product Description

The Mobil Super 1000 TM 15W-40 is premium mineral motor oil designed to provide a high level of performance and protection under most operating conditions. Mobil Super 1000 TM 15W-40 is primarily intended for use in Tata Motors Diesel Passenger Vehicles.

### Features and Benefits

Mobil Super 1000 TM 15W-40 provides very good engine protection and helps extend engine life. In addition, it helps provide:

- Excellent wear protection
- Excellent engine cleanliness

### Applications

Mobil Super 1000 TM 15W-40 has been developed to meet the latest specifications for engine oils required by Tata Motors. It offers long term engine protection from wear and sludge and deposit build-up. It is recommended by ExxonMobil for use in Tata Motors Passenger Cars and Multi Utility Vehicles where a product approved to their specification SS 6571 is specified.

### Specifications and Approvals

#### This product has the following approvals:

TATA MOTORS FOR PASSENGER CAR DIESELS

TATA MOTORS FOR MULTI UTILITY VEHICLES

#### This product meets or exceeds the requirements of:

API CG-4

API CF-4

API CH-4

API SL

### Properties and Specifications

Property	
Grade	SAE 15W-40
Density @ 15.6 C, g/ml, ASTM D4052	0.86
Flash Point, Cleveland Open Cup, °C, ASTM D92	234

Property	
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.4
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	104
Pour Point, °C, ASTM D97	-33
Viscosity Index, ASTM D2270	142

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,  
Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved