



## Mobil Delvac™ Light Commercial Vehicle E 10W-40

Mobil Commercial Vehicle Lube , Iceland

Light Commercial Vehicle Engine Oil

### Product Description

Mobil Delvac™ Light Commercial Vehicle E 10W-40 is a semi-synthetic engine oil that provides long engine life and excellent engine protection against sludge & we

Mobil Delvac™ Light Commercial Vehicle E 10W-40 provides excellent lubrication of diesel and gasoline engines operating in severe driving conditions ty encountered in city operations. This product is recommended by ExxonMobil for European engines for use in a wide range of traditional light-duty commercial vehi

### Features and Benefits

Mobil Delvac™ Light Commercial Vehicle E 10W-40 is formulated from high performance base oils and a superior balanced additive system to provide optimum performance in recent diesel and gasoline engines as well as older models. Key benefits include:

| Features   | Advantages and Potential Benefits   |
|--|---|
| Increased thermal and oxidation stability  | Help to reduced sludge build-up, deposits, and long oil and engine life         |
| Enhanced wear protection   | Helps towards long component and engine life                                    |
| Advanced piston deposit control  | Helps to keep engines clean with reduced maintenance costs and long engine life |
| Advanced soot handling to control viscosity increase, sludge build up, and filter pressure | Helps to enhance engine protection for long engine life                         |
| Enhanced low temperature pumpability   | Fast start up with reduced wear operating in low temperature climates           |

### Applications

ExxonMobil recommends Mobil Delvac™ Light Commercial Vehicle E 10W-40 for demanding driving conditions:

- Older engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Light trucks and vans
- Normal to occasionally severe operating conditions

### Specifications and Approvals

| This product has the following approvals: |
|---|
| VW 501 01                                 |
| VW 505 00                                 |

| This product is recommended for use in applications requiring: |
|--|
| MB-Approval 229.1  |

**This product meets or exceeds the requirements of:**

API SN PLUS

ACEA A3/B3

### Properties and Specifications

| Property   |            |
|--|------------|
| Grade  | SAE 10W-40 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92                          | 234        |
| Ash, Sulfated, mass%, ASTM D874  | 0.9        |
| Cold-Cranking Simulator, Apparent Viscosity @ -25 C, mPa.s, ASTM D5293 | 5400       |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445              | 95         |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445             | 14.2       |
| Density @ 15.6 C, g/ml, ASTM D4052                                     | 0.87       |
| Total Base Number, mgKOH/g, ASTM D2896                                 | 9.9        |
| Viscosity Index, ASTM D2270  | 155        |
| Pour Point, °C, ASTM D97   | -33        |

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2020

**ExxonMobil**

Exxon Mobil ESSO XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved