



Mobil™ Dexron-VI ATF

Mobil Passenger Vehicle Lube , Italy

Product Description

Mobil DEXRON-VI ATF is a high performance, synthetic blend formulation that meets or exceeds the stringent requirements of GM's DEXRON-VI specification and provides warranty protection for 2006 and newer GM vehicles. It also provides improved performance in older GM vehicles, wherever DEXRON is specified.

Features and Benefits

Advantages offered by Mobil DEXRON-VI ATF over Dexron/Mercon type transmission fluids:

- Extended fluid life
- Improved oxidation and thermal stability
- Optimized frictional properties that provide smooth gear shifting during low temperature operation and help prevent transmission vibration
- Outstanding resistance against sludge and deposit formation
- Improved anti-wear protection which contributes to extended transmission life
- Outstanding low temperature performance

Applications

Mobil DEXRON-VI ATF provides warranty protection for 2006 and newer GM vehicles.

Specifications and Approvals

This product has the following approvals:

GM DEXRON VI

This product meets or exceeds the requirements of:

ISUZU Power Steering Fluid

Properties and Specifications

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	214
Color, Visual	Red
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	30
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	5.85
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	11500

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

Esso Italiana s.r.l.

Via Castello della Magliana 25
00148, Roma, Italia

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.it/it-it/contact-us>

800.011723

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved