



Mobil Vactra™ Oil No.2 SLC

Mobil Industrial , Japan

Way and Slide Lubricants

Product Description

The Mobile Vactra™ Oil No.2 SLC is a slideway lubricant specifically designed for linear motion guides, ball screws and slideways of machine tools and metal processing machine. While the product achieves high-level performance as the slideway basic performance for preventing stick-slip and chatter, it provides corrosion and rust protection, oil-stain resistance, etc. Furthermore, with the excellent compatibility with aqueous coolants, this is the most suitable slideway lubricant for machine tools using coolants.

The Mobil Vactra Oil No.2 SLC has been developed as a new lubricant with enhanced adhesive property for slideways and the significantly enhanced adhesiveness on slideways prevents slideway lubricants from being washed away even when coolants are infiltrated to slideways. Particularly due to recent increase in the use of aqueous or solution type coolants with high-level washing performance, washing away of conventional slideway lubricants by coolants, occurrence of abnormal noise on slideways, increase in sliding resistance, stopping of operation by overload of sliding motors and in the decrease of machining accuracy have been identified. In such cases, use of the Mobil Vactra Oil No.2 SLC can improve the situations. By using this product, even in the case that an increase in the refueling frequency and amount of the slideway lubricants is inevitable.

Also in some cases, adhesive deposits may be formed due to attaching of coolants on slideways of machining tools using coolants, such deposit formation can be minimized by using the Mobil Vactra Oil No.2 SLC due to its excellent compatibility with coolants.

Furthermore, the excellent separability from coolants allows easy removing of sludge in the case of inclusion of Mobil Vactra Oil No.2 SLC in a coolant tank, and this contributes to maintaining of the performance of coolants and longer life through anti-biodegradability.

Features and Benefits

The Mobil Vactra Oil No.2 SLC has been developed and specifically designed to provide an extra margin of machinery protection by satisfying the stringent demands on slideways of machine tools. These oil series products exhibit excellent lubricity and load-carrying performance contributing significantly to improving the quality of machining parts. Furthermore, the Mobil Vactra Oil No.2 SLC has the following features by providing compatibility with coolants while maintaining excellent slideway performance and there are following potential benefits by the use.

Features	Advantages and Potential Benefits
Controlled frictional characteristics	Preventing the occurrence of chattering and lost motion and improving the processing accuracy
Excellent adhesiveness	- Protecting slideways by forming strong and stable coating and preventing washing out from slideways - Forming stable oil coating to the solution or aqueous type coolants that can easily wash away the slideway lubricants and ensuring smooth operation while maintaining the refueling intervals - Providing protection against fretting corrosion and corrosion abrasion to linear motion guide and ball screw lubricants
Excellent separability from coolants	Allowing easy elimination of sludges in a coolant tank, maintaining of coolant performance, and longer life due to anti-biodegradability
Compatibility with coolants and sludge protection	Controlling adhesive substance formation due to mixing of coolants in slideway lubricants
Compatibility with a wide range of metal materials	Providing compatibility with slideways with a combination of various materials and allowing product integration
Long term rust and corrosion protection	Preventing the deterioration of slideways in the presence of water and aqueous coolants

Applications

The Mobil Vactra Oil No.2 SLC is suitable for the following applications:

- Small to large size machine tool slideways which require VG 68 viscosity
- Brush application, forced lubrication, or hydrostatic circulation refueling systems
- Machine tools using aqueous coolants
- Lubrication of ball screws, linear motion guides (linear motion rolling bearings), head stocks and feeding screws
- Machine with shorter coolant replacement intervals due to mixing of slideway lubricants in the coolants
- Machine tools with the formation of adhesive substances on sliding surface and resultant negative effects in lubrication

- Machine tools with an inevitable increase in the refueling frequency and amount for the slideway lubricants due to the use of coolants

Typical Properties

Mobil Vactra Oil	No. 2SLC
ISO Viscosity Grade	68
Density @15°C, g/cm3	0.8791
Kinematic Viscosity@ 40°C, mm2/s	63.25
@100°C, mm2/s	8.877
Viscosity Index	115
Flash Point COC , °C	238
Pour Point, °C	-10.0

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Vactra are trademarks of Exxon Mobil Corporation, or one of its subsidiaries..

05-2020
ExxonMobil Japan Godo Kaisha
Shinagawa Grand Central Tower
2-16-4, Konan, Minato-Ku,
Tokyo, 108-8218,
Japan

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved