



Mobil Super™ SN 5W-30 K Concept

Mobil Passenger Vehicle Lube , Japan

Synthetic Motor Oil

Product Description

Mobil Super™ SN 5W-30 K-Concept is a synthetic motor oil, which provides excellent high temperature protection even under severe operating conditions. It is designed to help provide long engine life and outstanding protection in vehicles of all ages. The product provides outstanding protection against sludge, engine rust and corrosion under severe and low-temperature operating conditions and provides optimum viscosity and fluidity across a broad range of temperatures. Its low friction synthetic formulation increases engine efficiency and offers greater fuel economy.

Mobil Super SN 5W-30 K-Concept meets or exceeds the requirements of API SN, and is recommended especially for K-Concept light vehicles.

Features and Potential Benefits

- Helps extend engine life
- Outstanding wear protection
- Excellent high temperature protection to help keep engines cool
- Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts
- Excellent fuel economy

Applications

- Mobil Super SN 5W-30 K-Concept is recommended for gasoline fueled K-Concept light vehicles where a 5W-30 viscosity is required.
- Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SN

This product is recommended for use in applications requiring:
API CF

Typical Properties

Mobil Super SN 5W-30 K-Concept	Typicals
Density @15°C, kg/l	0.850
Viscosity @ 100°C, cSt	10.3
CCS @-30°C , cP	4000
MRV @-35°C, cP	20000
Viscosity Index	160

Mobil Super SN 5W-30 K-Concept	Typicals
Pour Point, °C	-33
Flash Point, °C, ASTM D 92	210

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021
ExxonMobil Japan Godo Kaisha
Shinagawa Grand Central Tower
2-16-4, Konan, Minato-Ku,
Tokyo, 108-8218,
Japan

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved