



Mobil Super™ 2000 High Mileage 10W-30

Mobil Passenger Vehicle Lube , Japan

Synthetic Technology Engine Oil

Product Description

Mobil Super™ 2000 High Mileage helps on long engine life and outstanding protection for vehicles with more than 60,000 Km. Formulated with seal conditioner, Super 2000 High Mileage helps prevent leaks and reduce oil consumption.

These oils protect against sludge, engine rust and corrosion under severe and low-temperature operating conditions.

Features and Benefits

- Helps extend engine life
- Contains seal conditioner to help prevent or control leaks and reduce oil consumption
- Helps protects older engines
- Outstanding wear protection under a wide variety of operating conditions
- Easy cold starting.

Applications

Mobil Super™ 2000 High Mileage 10W-30 is recommended for fuel economy cars and turbo charged cars which are recommended 10W-30, with high mileage 60,000 km.

Specifications and Approvals

This product meets or exceeds the requirements of:

API SN

Properties and Specifications

Property	
Grade	SAE 10W-30
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	63.5
Pour Point, °C, ASTM D97	-36
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	14900
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 ⁽⁶⁾ sec ⁽⁻¹⁾ , mPa.s, ASTM D4683	3
Ash, Sulfated, mass%, ASTM D874	0.9
Flash Point, Cleveland Open Cup, °C, ASTM D92	238
Density @ 15 C, g/ml, ASTM D4052	0.867

Property	
Viscosity Index, ASTM D2270	145
Total Base Number, mgKOH/g, ASTM D2896	8.1

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2023

ExxonMobil Japan Godo Kaisha

Shinagawa Grand Central Tower

2-16-4, Konan, Minato-Ku,



Tokyo, 108-8218,

Japan

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon Mobil  

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved