



Mobil Super™ Everyday Protection C2 5W-30

Mobil Passenger Vehicle Lube , South Korea

Synthetic Technology Engine Oil

Product Description

Mobil Super™ Everyday Protection C2 5W-30 is premium synthetic technology motor oil designed to provide everyday protection for cars under most operating conditions.

Features and Benefits

Mobil Super™ Everyday Protection C2 5W-30 is meticulously engineered for today's tougher engine specifications. It provides reliable engine protection in everyday driving and helps to extend engine life.

- Designed to provide reliable anti-wear protection
- Protection against LSPI (low speed pre-ignition) events in TGDl engines to help prolong engine life
- Helps to maintain engine cleanliness
- Compatible with most latest diesel particulate filters and gasoline catalytic converters

Applications

Mobil Super™ Everyday Protection C2 5W-30 is ideally suited for gasoline and diesel powered vehicles in common driving conditions such as highway driving and consistent speed conditions in everyday driving.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SN
API SN PLUS
ACEA C2

Properties and Specifications

Property	
Grade	SAE 5W-30
Viscosity Index, ASTM D2270	157
Total Base Number, mgKOH/g, ASTM D2896	7.7
Density @ 15.6 C, g/ml, ASTM D4052	0.854
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	9.9

Property	
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	57
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3
Pour Point, °C, ASTM D97	-53
Flash Point, Cleveland Open Cup, °C, ASTM D92	207
Ash, Sulfated, mass%, ASTM D874	0.7
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	21500

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020

Mobil Korea Lube Oil Inc.

Level 22, Seoul Square bd., Hangang-daero, Jung-gu, Seoul, Korea

+82-2-750-8700

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved