



Mobil™ Multipurpose ATF

Mobil Passenger Vehicle Lube , South Korea

Superior Performance Automatic Transmission Fluid

Product Description

Mobil Multipurpose ATF is a high performance, automatic transmission fluid designed to meet the service fill requirements for Asian, European and North American designed vehicles. Mobil Multipurpose ATF provides reliable performance including smooth & consistent all weather shifting and all-around lubrication protection of the transmission components. Use of Mobil Multipurpose ATF can lead to dependable longer transmission service life and a smooth driving experience.

Features and Benefits

Mobil Multipurpose ATF is formulated from selected high-quality base oils combined with an advanced additive system including special friction modifiers and lubricity agents. It is designed to control the transition from full-film to thin-film lubrication as a vehicles band and clutches are activated during shifting. Mobil Multipurpose ATF ensures consistent repeatable, smooth shifts under a broad range of driving conditions, temperatures and transmissions. Mobil Multipurpose ATF also offers the required oxidation stability designed to meet a more severe set of requirements for warranty protection in most late-model vehicles. Key features and benefits include:

- Excellent thermal and oxidation stability for long and consistent transmission performance
- Friction modifiers improve transmission efficiency and shifting performance
- Good film-strength and anti-wear properties reduce wear and maintain good transmission life
- Excellent low-temperature properties provide easier start-ups and improved lubrication at low ambient temperatures
- Effective foam control properties provide consistent shifting performance and reduce fluid losses in severe service
- Compatibility with all common seal materials helping the control of oil leakage
- Satisfies most new car requirements to give the user confidence

Specifications and Approvals

<b>This product has the following builder approvals:</b>
Allison TES-389

<b>This product is recommended by ExxonMobil for use in applications requiring:</b>
GM DEXRON III H
FORD MERCON
ALLISON C-4

Properties and Specifications

Property	
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	16200

Property	
Color, Visual	Red
Density @ 15 C, kg/l, ASTM D4052	0.86
Flash Point, Cleveland Open Cup, °C, ASTM D92	182
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	7
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	32
Pour Point, °C, ASTM D97	-51
Viscosity Index, ASTM D2270	176

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2023

Mobil Korea Lube Oil Inc.

Level 22, Seoul Square bd., Hangang-daero, Jung-gu, Seoul, Korea

+82-2-750-8700

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved