



Mobil 1 Extended Life 10W-60

Mobil Passenger Vehicle Lube , Kazakhstan
Advanced Full Synthetic Engine Oil

Product Description

Mobil 1 is the world's leading synthetic engine oil brand delivering our ultimate performance and protection.
Mobil 1 Extended Life 10W-60 is engineered for the specific demands of older vehicles.

Features and Potential Benefits

Mobil 1 Extended Life 10W-60 is engineered to help provide long lasting protection in higher mileage engines so you can get long life out of your vehicle.

- Extra seal conditioners to help prevent oil leaks
- Helps to reduce sludge build up to keep engines clean and prevent wear
- Outstanding/Excellent oil film thickness for extra protection in older engines
- Higher viscosity to help reduce oil burn off in older engines
- More anti-wear additives to help protect worn engines
- High performance basestocks for excellent all-round wear protection

Applications

Mobil 1 Extended Life 10W-60 has been designed to help provide the extra protection that older engines can demand. It is suitable for virtually all types of older v and operating conditions.

- Older vehicles
- Nearly all operating conditions, from mild to extreme
- An ideal product for Racing applications

Always consult your owner’s manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

Mobil 1 Extended Life 10W-60 meets or exceeds the requirements of:	
API SN/SM/SL	›
ACEA A3/B3, A3/B4	›

Mobil 1 Extended Life 10W-60 has the following builder approvals:	
VW 501 01 / 505 00	›
MB-Approval 229.1	›

According to ExxonMobil, Mobil 1 Extended Life 10W-60 is of the following quality level	10W-60
API CF	X

Typical Properties

Mobil 1 Extended Life 10W-60	
Viscosity, cSt (ASTM D445)	

Mobil 1 Extended Life 10W-60	
@ 40° C	152.7
@ 100° C	22.7
Viscosity Index	178
Sulfated Ash, wt% (ASTM D874)	1.4
Phosphorous, wt% (ASTM D4951)	0.13
Flash Point, °C (ASTM D92)	234
Density @15.6 °C g/ml (ASTM D4052)	0.86
Total Base Number (ASTM D2896)	11.8
MRV at -30 °C, cP (ASTM D4684)	25,762
HTHS Viscosity, mPa•s @ 150 °C (ASTM D4683)	5.7

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet, or provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, please take care to protect the environment.

Mobil , Mobil 1 and the Pegasus designare trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

.

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved