



Mobil 1™ ESP 0W-30

Mobil Passenger Vehicle Lube , Sri Lanka

Advanced Multigrade Synthetic Four-Stroke Motorcycle Engine Oil

Product Description

Mobil 1™ ESP 0W-30 is an advanced full synthetic engine oil designed to provide exceptional engine performance, wear protection and cleaning power.

Mobil 1™ ESP 0W-30 has been expertly engineered to help prolong the life and maintain the efficiency of emission systems in both diesel and gasoline powered automobiles.

Mobil 1™ ESP 0W-30 is recommended by TATA Motors for all BS4 and BS6 vehicles with Tata powertrains.

Mobil 1™ ESP 0W-30 also meets or exceeds the requirements of many leading industry and car manufacturers' standards required for newer modern diesel and gasoline powered passenger car engines.

Features and Benefits

Mobil 1™ ESP 0W-30 is made with a proprietary blend of leading edge components formulated to be fully compatible with after treatment devices, like DOC, DPF, SCR. Mobil 1™ ESP 0W-30 has been designed to help deliver outstanding performance and protection in conjunction with potential fuel economy benefits. Key features and potential benefits include:

Features	Advantages and Potential Benefits
Low Ash Content	Helps to reduce particulate build up in Diesel Particulate Filters
Low Sulfur and Phosphorous content	Helps to reduce poisoning of Gasoline Catalytic Converters
Active cleaning agents	Helps to reduce deposits and sludge build-up to enable long and clean engine life
Outstanding thermal and oxidation stability	Helps to reduce oil aging allowing extended drain interval protection
Low oil consumption	Less hydrocarbon pollution
Enhanced frictional properties	Potentially aids fuel economy
Excellent low temperature capabilities	Quick cold weather starting and ultra-fast protection helps to extend engine life

Applications

Mobil 1™ 1 ESP 0W-30 is recommended for many types of modern automobile engines, especially high-performance gasoline and diesel engines found in the latest passenger cars, SUVs and light vans.

Mobil 1™ 1 ESP 0W-30 is especially suitable for extreme conditions, where conventional oil often may not perform. It is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Specifications and Approvals

This product has the following approvals:

Porsche C30

MB-Approval 229.52

MB-Approval 229.51

MB-Approval 229.31

VW 504 00

VW 507 00

This product meets or exceeds the requirements of:

API SP ENGINE TEST REQUIREMENTS

API SN PLUS ENGINE TEST REQUIREMENTS

API SN Engine Test Requirements

ACEA C3

Properties and Specifications

Property	
Grade	SAE 0W-30
Total Base Number, mgKOH/g, ASTM D2896	8.4
Density @ 15.6 C, g/ml, ASTM D4052	0.845
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	12.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	65
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.5
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	18400
Ash, Sulfated, wt%, ASTM D874	0.8
Flash Point, °C, ASTM D92	230
Pour Point, °C, ASTM D97	-51

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved