



Mobil Delvac™ Super 1400 15W-40

Mobil Commercial Vehicle Lube , Lithuania

High Performance Diesel Engine Oil

Product Description

Mobil Delvac™ Super 1400 15W-40 is a high performance diesel engine oil that provides protection for diesel engines operating under severe service conditions for both on- and off-highway applications. Mobil Delvac Super 1400 15W-40 is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying and agricultural industries

Features and Benefits

| Features | Advantages and Potential Benefits |
|-----------------------------------|--|
| Thermal and oxidation stability | Helps to control sludge build-up and deposits |
| TBN reserve | Helps to control deposits |
| Stay-in-grade shear stability | Helps to reduce oil consumption and to provide wear protection |
| Excellent detergency/ dispersancy | Helps to protect and to maintain engines clean |
| Component compatibility | Long gasket and seal life |

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment of European, Japanese and American manufacturers in line with owner manual recommendations
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying and agriculture

Specifications and Approvals

| This product has the following approvals: |
|---|
| MB-Approval 228.3 |
| MTU Oil Category 2 |

| This product is recommended for use in applications requiring: |
|--|
| ACEA B2 |
| ACEA E3 |

This product is recommended for use in applications requiring:

API CF

API CF-4

API CG-4

API SH

MAN M 3275-1

RENAULT TRUCKS RD

RENAULT TRUCKS RD-2

VOLVO VDS-2

This product meets or exceeds the requirements of:

API CH-4

API SJ

Properties and Specifications

| Property | |
|--|------------|
| Grade | SAE 15W-40 |
| Cold-Cranking Simulator, Apparent Viscosity @ -20 C, mPa.s, ASTM D5293 | 5800 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 110 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 14.6 |
| Density @ 15 C, lb/USg, ASTM D4052 | 0.87 |
| Total Base Number, mgKOH/g, ASTM D2896 | 9.2 |
| Viscosity Index, ASTM D2270 | 136 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 225 |
| Pour Point, °C, ASTM D97 | -36 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>


All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2020

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect

product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

The ExxonMobil logo, featuring the word "Exxon" in a bold, sans-serif font and "Mobil" in a similar font, with a stylized "X" connecting the two.The Exxon logo, which is a small, stylized "X" inside a circle.The Mobil logo, which is the word "Mobil" in a bold, sans-serif font.The Esso logo, which is the word "Esso" in a bold, sans-serif font, enclosed within an oval border.The XTO logo, which is the letters "XTO" in a bold, sans-serif font, with a stylized "X" and "O" that are connected.

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved