



Mobil Super™ 3000 Formula VC 0W-30

Mobil Passenger Vehicle Lube , Latvia

Mobil passenger-vehicle-lube High performance engine oil

Product Description

Mobil Super™ 3000 Formula VC 0W-30 is a high performance full SAPS engine oil specifically designed for servicing modern gasoline, diesel and hybrid cars fr Volvo Cars Group.

Features and Benefits

- Excellent low temperature capabilities for reliable cold weather starting allowing fast engine start.
- Provides effective lubrication in a wide range of operating temperatures and driving conditions.
- Prolongs engine life by preventing harmful deposits and sludge build-up on the engine parts.
- Provides fuel economy potential according to ACEA A5/B5 and A7/B7 test sequence
- Contributes to Low Speed Pre-Ignition (LSPI) protection for turbocharged gasoline DI engines.

Applications

Mobil Super 3000 Formula VC 0W-30 is recommended for use in Volvo B5, B6, B8, D5, petrol and diesel engines, and D82 and D87 hybrid drive engines, with or v extended service intervals.

Owner's manual should be consulted for recommended viscosity grades and specification.

Specifications and Approvals

This product has the following approvals:
VOLVO 95200377

This product meets or exceeds the requirements of:
API SL
API SM
API SP
ACEA A5/B5
ACEA A7/B7

Properties and Specifications

Property	
Grade	SAE 0W-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	234

Property	
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	53.4
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	9.9
Density @ 15.6 C, g/ml, ASTM D4052	0.841
Viscosity Index, ASTM D2270	175
Pour Point, °C, ASTM D97	-42

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTOMOBILE

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved