



Mobil Super™ 1000 10W-30

Mobil Passenger Vehicle Lube , Myanmar

Everyday Protection Premium Mineral Engine Oil

Product Description

Mobil Super™ Everyday Protection is a premium mineral engine oil that delivers proven protection to extend engine life. Formulated with the ExtEngine™ molecule, an age-defying, anti-wear ingredient, Mobil Super™ Everyday Protection reacts to engine-damaging stress by creating a long-lasting protective barrier for 65%[^] better wear protection. Mobil Super™ Everyday Protection meets or exceeds the requirements of the highest engine oil performance standards. Suitable for older Japanese and Korean cars including Toyota, Honda, Nissan, Daihatsu, Suzuki, Mitsubishi, Hyundai, and more.

Features and Benefits

- Premium mineral engine oil for everyday protection
- ExtEngine molecules for a long-lasting protective barrier to extend engine life
- 65% better engine wear protection[^]
- Meets or exceeds the latest industry standards

[^] Based on Sequence IVB (Iron Wear) test result vs. API SP engine test.

Applications

ExxonMobil recommends Mobil Super™ Everyday Protection for daily driving under normal conditions:

- Older engine technologies
- Gasoline and diesel engines
- Passenger cars, SUVs, light trucks and vans

Always consult your owner's manual to check the recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
API SP
API SN PLUS
API SN
API SM
API SL
ILSAC GF-6A
API CF

Properties and Specifications

Property	
Grade	SAE 10W-30
Viscosity Index, ASTM D2270	149
Total Base Number, mgKOH/g, ASTM D2896	7.5
Density @ 15.6 C, g/ml, ASTM D4052	0.858
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	64
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	8900
Ash, Sulfated, mass%, ASTM D874	0.8
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	226

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2022

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved