



Mobil Delvac MX™ F2 15W-40

Mobil Commercial Vehicle Lube , Mexico

High Performance Diesel Engine Oil

Product Description

Mobil Delvac MX™ F2 15W-40 is a high performance diesel engine oil that helps extend engine life in severe on and off highway applications. The advanced chem these products delivers exceptional performance in both modern, high-output engines including those with Exhaust Gas Recirculation (EGR), as well as older e operating on either low or high sulfur fuels. As a result, Mobil Delvac MX™ F2 15W-40 meets or exceeds the API CI-4 PLUS service category.

Mobil Delvac MX™ F2 15W-40 is recommended by ExxonMobil for use in a wide range of heavy duty applications and operating environments found in the tr mining, construction, quarrying, marine and agricultural industries. These products will provide outstanding protection in the most demanding diesel engi Caterpillar, Cummins, Detroit, Mack, Navistar, Volvo, and others. Mobil Delvac MX™ F2 15W-40 also meets or exceeds the API SL specification for gasoline engin mixed fleets.

The outstanding performance reserve of Mobil Delvac MX™ F2 15W-40 is the result of extensive cooperative development work with major Original Equi Manufacturers (OEMs) and advanced additive chemistry with patented Trimer technology. These enhancements assure excellent control of oil thickening due t build-up and exposure to higher temperatures and provide outstanding resistance to oxidation, corrosion, wear, and high temperature deposits.

Features and Benefits

Modern high output diesel engines including those using EGR technology generate higher levels of soot and run at higher temperatures than older, naturally asp engines, which significantly increases the demands on engine lubricants. These engine designs reduce oil consumption, resulting in less fresh oil makeup to ref depleted additives. Top piston rings are located higher on the piston bringing the oil film closer to the combustion chamber where higher temperatures increase th stress on the lubricant. Higher fuel injector pressure and retarded timing improve exhaust emission control, but also increase engine temperatures and increas loads, including those engines operating with EGR. The key benefits include:

Features	Advantages and Potential Benefits
Outstanding thermal and oxidation stability	Reduced low temperature sludge build-up and high temperature deposits
Extended TBN reserves	Improved soot handling and extended drain intervals
Stay-in-grade shear stability	Reduced oil consumption and wear protection Maintains viscosity in severe, high temperature service
Excellent low temperature pumpability	Easier engine start-up and reduced wear
Superb resistance to corrosion	Longer life of critical wear surfaces

Applications

Recommended by ExxonMobil for use in:

- High performance diesel applications including pre-2007 turbo-charged, low emission engines designs, including those featuring EGR technology
- On highway applications operating in both high speed/high load and short haul pick-up/delivery
- Off highway applications operating in severe low speed/heavy load conditions
- Modern marine high-speed diesel engines, including Caterpillar, Cummins, Volvo, Daihatsu, and Yanmar.
- High performance gasoline engines and mixed fleet operators
- Diesel-powered equipment from American and Japanese OEMs
- On highway heavy duty trucking and off highway including: construction, mining, quarrying, and agriculture

Specifications and Approvals

This product has the following approvals:

MACK EO-M PLUS

VOLVO VDS-3

Detroit Detroit Fluids Specification 93K214

DQC II-18

Mack EO-N

MB-Approval 228.3

RENAULT TRUCKS RLD-2

DTFR 15B110

This product is recommended for use in applications requiring:

API CG-4

API CF

ACEA E5-02

VOLVO VDS-2

MACK EO-M

MAN M 3275-1

CUMMINS CES 20072

CUMMINS CES 20071

API CF-4

RENAULT TRUCKS RLD

This product meets or exceeds the requirements of:

API CI-4 PLUS

API CI-4

API CH-4

API SL

API SJ

Caterpillar ECF-2

Cummins CES 20078

CUMMINS CES 20077

This product meets or exceeds the requirements of:	
CUMMINS CES 20076	
ACEA E7	
Caterpillar 1E1867	
Ford WSS-M2C171-D	

Properties and Specifications

Property	
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	15.3
Density @ 15 C, kg/l, ASTM D4052	0.870
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	110
Flash Point, °C, ASTM D92	223
Viscosity Index, ASTM D2270	145
Pour Point, °C, ASTM D97	-36
Total Base Number, mgKOH/g, ASTM D2896	11

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, Ciudad de Mexico

(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect pro performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without nc All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intende override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved