



Mobil Super™ 3000 X2 5W-40

Mobil Passenger Vehicle Lube , Malaysia
Full Synthetic Engine Oil

Product Description

Mobil Super™ 3000 X2 5W-40 is brought to you by the makers of Mobil 1. This full synthetic engine oil is tailored for smoother acceleration and provides outstanding engine wear protection even under the most demanding driving conditions.

Features and Benefits

- Suitable for European, Japanese and Korean gasoline and diesel engines
- Formulated with Heat-Activated Anti-Wear Molecules™ technology which provides superior engine protection.
- Outstanding engine cleanliness.
- Outstanding high temperature protection.
- Outstanding low temperature protection.

Applications

- Suitable for both Gasoline and Diesel Engines
- Passenger cars, SUVs, light trucks and vans
- Turbo-Chargers and Direct Injection engines
- Highway cruising and stop and go city driving

Specifications and Approvals

This product has the following approvals:
MB-Approval 229.3
RENAULT RN0700
RENAULT RN0710
VW 502 00
VW 505 00
This product is recommended for use in applications requiring:
API CF
GM-LL-B-025
This product meets or exceeds the requirements of:
ACEA A3/B3

This product meets or exceeds the requirements of:

API SJ

API SL

API SM

API SN

Properties and Specifications

Property	
Grade	SAE 5W-40
Viscosity Index, ASTM D2270	174
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	47000
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	85
HTHS Viscosity, 150 C 1x10 (6) sec (-1), cP, CEC L-36-A-97	3.7
Density @ 15 C, g/ml, ASTM D4052	0.856
Total Base Number, mgKOH/g, ASTM D2896	10.1
Ash, Sulfated, mass%, ASTM D874	1.09
Flash Point, Cleveland Open Cup, °C, ASTM D92	222
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.2
Pour Point, °C, ASTM D97	-42

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2023

1-800-81-6233

SEALubeline@exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved