



## Mobil™ Gear Oil FE 75W

Mobil Passenger Vehicle Lube , Malaysia

Manual Automotive Transmission Fluid

### Product Description

Mobil Gear Oil FE 75W is a high performance gear oil blended from high quality mineral base oils and an advanced additive system to meet Peugeot's & Citroën's specification. Mobil Gear Oil FE 75W is specially developed for PSA's (Peugeot / Citroën) manual gearboxes with integrated differentials. This product fully replaces Mobil Gear Oil BV 75W-80.

### Features and Benefits

Mobil Gear Oil FE 75W is resistant to high temperature and protects from oxidation. Mobil Gear Oil FE 75W provides excellent cold flow and smooth gear shifting. Mobil Gear Oil FE 75W provides fuel economy benefits (\*) over Mobil Gear Oil BV 75W-80 (PSA Factory Fill reference B71 2330) while maintaining the same durability performance.

(\*) fuel economy gain estimated by PSA Peugeot Citroën to 0.45% in MVEG cycle on MC, BE and ML transmissions) vs. Mobil Gear Oil BV 75W-80.

### Applications

Mobil Gear Oil FE 75W is the only gear oil used for factory fill for all Peugeot & Citroën manual gearboxes fitted into PSA models in Europe. It is also fully backward compatible and suitable for use in all existing Peugeot and Citroën Manual Transmissions in Europe.

### Specifications and Approvals

**This product has the following approvals:**

Peugeot/Citroën Automobiles B71 2310

### Properties and Specifications

Property	
Grade	SAE 75W
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	6.4
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	35
Viscosity Index, ASTM D2270	134
Pour Point, °C, ASTM D97	-45
Density @ 15.6 C, g/cm <sup>3</sup> , ASTM D4052	0.8820

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2021

1-800-81-6233

SEALubeline@exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved