

Mobil Super™ 2000 X1 10W-40

Mobil Passenger Vehicle Lube , Namibia

Premium Semi-Synthetic Passenger Vehicle Motor Oil

Product Description

Mobil Super™ 2000 engine oils are premium engine oils and engineered to provide an excellent level of protection.

Mobil Super 2000 x1 10W-40 is formulated for city driving conditions of gasoline and diesel vehicles including passenger cars, light commercial vehicles and vans wide range of temperatures. Good wear protection and engine cleanliness helps to prolong engine life.

Features and Benefits

Mobil Super 2000 x1 10W-40 provides:

- Effective sludge prevention
- Good engine cleanliness
- Robust wear protection
- High temperature protection

Applications

Mobil Super 2000 products are formulated to give you confidence of protection beyond that of conventional oils. Mobil Super 2000 x1 10W-40 is recommended fc

- Older engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light commercial vehicles and vans
- Highway cruising and stop and go city driving
- Normal to occasionally severe operating conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
VW 501 01
VW 505 00
AVTOVAZ (LADA cars)

This product is recommended for use in applications requiring: API CF MB 229.1

This product meets or exceeds the requirements of:

This product meets or exceeds the requirements of:
API SL
API SM
API SN
API SJ
API SN PLUS
ACEA A3/B3

Properties and Specifications

Property	
Grade	SAE 10W-40
Density @ 15 C, g/ml, ASTM D4052	0.867
Flash Point, Cleveland Open Cup, °C, ASTM D92	234
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.2
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	95
Pour Point, °C, ASTM D97	-33

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.as

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

