



Mobil Super 3000 Formula F 5W-20

Mobil Passenger Vehicle Lube , Norway

High Performance Motor Oil

Product Description

Mobil Super 3000 Formula F 5W-20 is developed to meet the Ford requirement "Ford WSS-M2C948-B". Ford WSS-M2C948-B is a specific requirement for the EcoBoost 1.0L, 3 cylinders engines, the oil meeting Ford WSS-M2C948-B can be used for most gasoline Ford engines as mentioned in the applications.

Features and Benefits

Mobil Super 3000 Formula F 5W-20 is a standard ash engine oil with low High Temperature High Shear (HTHS) viscosity below 2.9 cP. The product is industry tested so you can trust it will deliver dependable performance for your vehicle's engine.

Applications

Mobil Super 3000 formula F 5W-20 can be used for all Ford gasoline engines with the exception of Ford KA (From MY 2009) and Ford Focus RS (MY 2004.75).

Owner's manual should be consulted for recommended viscosity grades and specification

Specifications and Approvals

This product meets or exceeds the requirements of:

API SN

Ford WSS-M2C948-B

Properties and Specifications

Property	
Grade	SAE 5W-20
Ash, Sulfated, mass%, ASTM D874	0.8
Density @ 15 C, g/cm ³ , ASTM D1298	0.851
Flash Point, °C, ASTM D92	230
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	7.9
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	42.4
Phosphorus, mass%, ASTM D4951	0.08
Pour Point, °C, ASTM D97	-36

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

Mobil Oil AS

Drammensveien 149, Postboks 350 Skøyen

N-0213 OSLO

(+47) 22 66 30 30


<http://www.mobil.no>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2021 Exxon Mobil Corporation. All Rights Reserved