



Mobil Delvac 1™ ESP 5W-40

Mobil Commercial Vehicle Lube , New Zealand

High Performance Advanced Synthetic Formula Low Ash Diesel Engine Oil

Product Description

Mobil Delvac 1™ ESP 5W-40 is an advanced synthetic heavy duty diesel engine oil that helps extend engine life while providing long drain capability¹ and potent economy² for modern and latest diesel engine technology operating in severe applications. This product is formulated to deliver exceptional performance in mode older, hard working, engines, including those with emission control systems. Mobil Delvac 1 ESP 5W-40 is recommended for use in a wide range of heav applications and operating environments found in the on-road transport and off-road mining, forestry, construction, and agricultural industries.

The outstanding performance of Mobil Delvac 1 ESP 5W-40 is the result of extensive cooperative development work of ExxonMobil with major equipment builde application of the latest lubrication technology. As a result, this product meets or exceeds the requirements of the latest API and ACEA industry specifications for engine oils, as well as the requirements of many major American, and European engine manufacturers.

¹ Please refer to the owners handbook for OEM application requirements and oil drain intervals for your vehicle or equipment.

² Compared to an SAE 15W-40 engine oil. Actual savings are dependent on vehicle engine type, outside temperature, driving conditions, and your current engine oil viscosity.

Features and Benefits

Mobil Delvac 1™ ESP 5W-40 is an outstanding lubricant solution for modern and latest engine technology equipped with emission after-treatment. It was develop ExxonMobil to maintain unsurpassed oxidation stability³ while also delivering exceptional low temperature fluidity and pumpability for smooth starting in cold dc -35°C. This feature, in combination with the sophisticated additive system, ensures exceptional engine wear performance and supports long engine life. The lc formulation protects at the same time all exhaust after-treatment devices to maintain cleaner air requirements. The advanced engine cleanliness performance pr deposits and keeps the engine running like new for long and efficient engine life.

³ Based on PC-11 industry test data.

Features	Advantages and Potential Benefits
Excellent low temperature pumpability	Reliable engine start and wear protection at low temperatures
Step out wear protection	Reduced engine wear to promote long engine life
Unsurpassed oxidation stability ³	Long oil drain intervals and prevention of deposits
Superb resistance to corrosion	Protection of critical engine surfaces in humid environments

Applications

Recommended by ExxonMobil for use in:

- Most engine generations up to latest and most sophisticated high performance diesel engines with turbo-charger, direct injection and low emission di featuring all types of exhaust after-treatment technology
- On-highway engines operating in both high speed/high load and stop-and-go conditions
- Off-highway engines operating in severe low speed/heavy load conditions
- Most diesel powered equipment from American and European equipment builders
- High performance gasoline engines and mixed fleets
- Refrigeration units

Specifications and Approvals

This product has the following approvals:
Detroit Fluids Specification 93K218
Detroit Detroit Fluids Specification 93K222
MACK EOS-4.5
MB-Approval 228.31
MTU Oil Category 2.1
VOLVO VDS-4.5
RENAULT TRUCKS RLD-3
DTFR 15C100

This product meets or exceeds the requirements of:
API CK-4
API CJ-4
API CI-4 PLUS
API CI-4
API CH-4
API SM
API SN
JASO DH-2
Caterpillar ECF-3
Cummins CES 20081
Cummins CES 20086
ACEA E7
ACEA E11-22

Properties and Specifications

Property	
Grade	SAE 5W-40
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	84
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13.8

Property	
Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293	6510
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	16800
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.8
Viscosity Index, ASTM D2270	169
Ash, Sulfated, mass%, ASTM D874	1
Total Base Number, mgKOH/g, ASTM D2896	12
Pour Point, °C, ASTM D97	-48
Flash Point, Cleveland Open Cup, °C, ASTM D92	233
Density, 15.6C, g/cm3, ASTM D4052	0.852

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024
Mobil Oil New Zealand Limited
164-188 Beaumont St
Auckland
New Zealand

+ 64 4 498 4000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect pro performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without nc All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intende override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved