



Mobilube HD Plus 80W-90, 85W-140

Mobil Commercial Vehicle Lube , New Zealand

Extra High Performance Commercial Gear Lubricants

Product Description

Mobilube HD Plus 80W-90 and 85W-140 are extra high performance commercial gear lubricants formulated from select base oils and an advanced additive system. These lubricants are engineered for performance in heavy-duty commercial transmissions, axles, and final drives where extreme pressures and shock loading are expected. They provide excellent chemical and thermal stability at elevated bulk oil temperatures, good performance at low temperatures, and have demonstrated good rust protection resulting from water contamination and wet conditions. They are recommended by ExxonMobil for applications where API GL-5 and MT-1 service is required.

Features and Benefits

Today's heavy equipment applications place higher performance demands on drive train lubricants. Higher speeds, higher torque, and heavier loads require improved formulations to maximise equipment life and optimise operating costs. Longer service intervals place additional demands on the gear lubricant. Mobilube HD Plus gear lubricants are engineered to meet these challenges. The key benefits include:

Features	Advantages and Potential Benefits
Excellent thermal stability and resistance to high temperature oxidation	Extended gear and bearing life due to minimal deposits and longer seal life
Good protection against low speed/high torque wear and against high speed scoring	Increased load carrying capability and reduced operating costs
Excellent rust, staining, and corrosion protection	Reduced wear and longer component life
Effective low temperature lubrication	Reduced wear and ease of start-up
Wide multipurpose capability	Reduced number of gear lubricants to simplify inventory and minimize misapplication
Good resistance to foaming	Maintains film strength for effective lubrication
Compatible with typical automotive seals and gaskets	Minimum leakage and reduced contamination

Applications

Recommended by ExxonMobil for use in:

- Heavy-duty manual transmissions, axles, and final drives requiring API GL-5 and MT-1 level performance
- On-highway light and heavy-duty trucks, busses, vans, and cars
- Off-highway industries including: construction, mining, quarrying, and agriculture
- Other heavy-duty industrial and automotive applications involving hypoid and other gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque conditions prevail
 - Initial fill, top-off, and refill of enclosed commercial gearing in manual or semiautomatic transmissions where gear lubricants are recommended including drive axles and final drives
- Not recommended for applications requiring API GL-4 Level performance
- Not intended for transmissions for which engine oil or automatic transmission fluids are recommended

Specifications and Approvals

This product has the following approvals:	80W-90	85W-140
Mack GO-J	X	X
SAE J2360	X	
Volvo 97321	X	X

This product is of quality level, but not approved:	80W-90	85W-140
MIL (US) MIL-PRF-2105E	X	X

This product meets or exceeds the requirements of the following industry specification:	80W-90	85W-140
API GL-5	X	X
API MT-1	X	X
Meritor O-94	X	
Scania STO 1:0	X	X

This product meets or exceeds the requirements of:	80W-90	85W-140
Meritor O-94		X

Properties and Specifications

Property	80W-90	85W-140
Grade	SAE 80W-90	SAE 85W-140
Density @ 15 C, kg/l, ASTM D4052	0.895	0.903
Flash Point, Cleveland Open Cup, °C, ASTM D92	210	230
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14	25.4
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	132	333
Pour Point, °C, ASTM D97	-27	-18

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

Mobil Oil New Zealand Limited
164-188 Beaumont St
Auckland
New Zealand

+ 64 4 498 4000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved