



Mobil™ Formula S 5W-30

Mobil Passenger Vehicle Lube , New Zealand

Mobil passenger-vehicle-lube

Product Description

Mobil Formula S 5W-30 is a premium semi-synthetic engine oil, designed to provide an excellent level of protection and performance.

Features and Benefits

Mobil Formula S 5W-30 provides

- Excellent fuel economy
- Outstanding wear protection
- Excellent engine cleanliness
- High temperature protection

Applications

Mobil Formula S 5W-30 is suitable for use in gasoline and LPG powered vehicles. It is ideally suited for normal to occasionally severe operating conditions and highway cruising.

Specifications and Approvals

This product meets or exceeds the requirements of:	
API SP	
API SN PLUS	
API SN	
ILSAC GF-6A	
FORD WSS-M2C961-A1	

Properties and Specifications

Property	
Grade	SAE 5W-30
Viscosity Index, ASTM D2270	151
Pour Point, °C, ASTM D97	-39
Ash, Sulfated, mass%, ASTM D874	0.8

Property	
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	16400
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	63
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.3
Density @ 15.6 C, g/ml, ASTM D4052	0.859
Total Base Number, mgKOH/g, ASTM D2896	7.5
Flash Point, Cleveland Open Cup, °C, ASTM D92	228

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2022
Mobil Oil New Zealand Limited
164-188 Beaumont St
Auckland
New Zealand

+ 64 4 498 4000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved