



## Mobil Super™ 3000 Formula V 5W-30

Mobil Passenger Vehicle Lube , New Zealand

High Performance Engine Oil

### Product Description

Mobil Super™ 3000 Formula V 5W-30 is a low ash high performance motor oil designed to meet the demanding requirements of extended service life whilst still contributing towards fuel economy and superior engine cleanliness.

### Features and Benefits

Mobil Super 3000 Formula V 5W-30 delivers excellent high and low temperature wear-protection and improved engine cleanliness.

Key features and benefits:

- Extended service interval as per VW requirements.
- Helping achieve fuel economy (as per ACEA C3).
- Improved engine internal cleanliness to maintain engine efficiency over life of vehicle.
- Fast circulation and protection.
- Full compatibility with most Diesel Particulate Filters and Catalytic Convertors.

### Applications

Mobil Super 3000 Formula V 5W-30 has been designed to meet the needs of the latest engine requirements of the VW Audi group where extended drain is required in conjunction with electronic service indicators with VW extended drain service schedule.

### Specifications and Approvals

<b>This product has the following approvals:</b>
BMW Longlife 04
MB-Approval 229.31
MB-Approval 229.51
VW 504 00
VW 507 00

### Properties and Specifications

Property	
Grade	SAE 5W-30
Ash, Sulfated, mass%, ASTM D874	0.8
Density @ 15 C, g/ml, ASTM D1298	0.852
Flash Point, Cleveland Open Cup, °C, ASTM D92	236
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	11.65
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	66
Pour Point, °C, ASTM D97	-45
Total Base Number, mgKOH/g, ASTM D2896	9
Viscosity Index, ASTM D2270	177
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	17100

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

Mobil Oil New Zealand Limited  
164-188 Beaumont St  
Auckland  
New Zealand

+ 64 4 498 4000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2021 Exxon Mobil Corporation. All Rights Reserved