



## **Mobil™ Dexron-VI ATF**

Mobil Passenger Vehicle Lube , New Zealand

Automatic Transmission Fluid

### **Product Description**

Mobil DEXRON-VI ATF is a high performance, synthetic blend formulation that meets or exceeds the stringent requirements of GM's DEXRON-VI specification. It also provides improved performance in older GM vehicles, wherever DEXRON is specified.

### **Features and Benefits**

Advantages offered by Mobil DEXRON-VI ATF over Dexron/Mercon type transmission fluids:

- Extended fluid life
- Improved oxidation and thermal stability
- Optimized frictional properties that provide smooth gear shifting during low temperature operation and help prevent transmission vibration
- Outstanding resistance against sludge and deposit formation
- Improved anti-wear protection which contributes to extended transmission life
- Outstanding low temperature performance

### **Applications**

Mobil DEXRON-VI ATF is Suitable for Use in vehicles requiring:

- Aisin Warner AW-1
- General Motors DEXRON-II and DEXRON-III
- Honda ATF-DW-1 and ATF-Z1
- Hyundai/Kia SP-II, SP-III, SP-IV and NWS-9638
- Isuzu Besco ATF-II, ATF-III, ATF SP, SCS Fluid
- JASO 1A-LV (M315)
- Mazda ATF M-III and ATF M-V
- Mitsubishi ATF-J2, ATF-J3, SP-II, SP-III, SP-IV
- Nissan Matic Fluid D, Matic Fluid K, Matic Fluid J and Matic Fluid S
- Subaru ATF, ATF-HP, ATF 5AT
- Toyota ATF T-III, T-IV, WS
- Voith 55.6335.xx (G607)
- Volkswagen/Audi Part #G 055 540 (A2)
- Volvo Part No. 1161521, 1161540/1161640

**Specifications and Approvals**

<b>This product has the following approvals:</b>
GM DEXRON VI

<b>This product meets or exceeds the requirements of:</b>
ISUZU Power Steering Fluid

**Properties and Specifications**

Property	
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	29.5
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	5.83
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	11500
Color, Visual	Red
Flash Point, Cleveland Open Cup, °C, ASTM D92	220

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2021

Mobil Oil New Zealand Limited  
164-188 Beaumont St  
Auckland  
New Zealand

+ 64 4 498 4000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil Esso XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved