



Mobil Delvac 25W-60

Mobil Commercial Vehicle Lube , Peru

High Performance Diesel Engine Oil

Product Description

Mobil Delvac™ 25W-60 is a high viscosity, high performance diesel engine oil that provides proven protection for diesel engines operating in severe service applica

Mobil Delvac™ 25W-60 is formulated from quality base stocks combined with performance additives, which help protect against the formation of sludge and corr

Features and Benefits

- Helps to reduce engine wear and corrosion in higher mileage vehicles
- Protects under a wide variety of operating conditions, especially high temperatures
- Helps reduce oil leakage due to the thick oil film
- Reduce oil consumption

Applications

Mobil Delvac™ 25W-60 is recommended by ExxonMobil for higher mileage vehicles including turbo charged, super charged, fuel injected, multi-valve and nc aspirated engines.

Before using Mobil Delvac™ 25W-60, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classificati

Specifications and Approvals

This product is recommended for use in applications requiring:	
API CF-4	
This product meets or exceeds the requirements of:	
API SL	
API SJ	

Properties and Specifications

Property	
Grade	SAE 25W-60
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	246

Property	
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	22.9
Pour Point, °C, ASTM D97	-16
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	215
Total Base Number, mgKOH/g, ASTM D2896	8.2
Viscosity Index, ASTM D2270	115
Density @ 15 C, g/ml, ASTM D1298	0.89

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020
Terpel Comercial del Perú S.R.L.
Av. Jorge Basadre Grohmann 347,
Interior 1005, San Isidro
Lima, Perú
24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved