



## Mobil Delvac Modern™ 15W-40 Full Protection

Mobil Commercial Vehicle Lube , Peru

Mobil commercial-vehicle-lube

### Product Description

Mobil Delvac Modern™ 15W-40 Full Protection is a synthetic technology, diesel engine oil that helps extend engine life, allowing you to run your business with confidence. This product meets or exceeds original equipment manufacturer (OEM) requirements and delivers high performance in both on and off-highway applications.

Fully backward compatible, Mobil Delvac Modern 15W-40 Full Protection delivers exceptional performance in both newer and older heavy duty engine designs. Accordingly, this oil meets or exceeds the requirements of API CK-4, CJ-4, CI-4 PLUS, CI-4 and CH-4 service categories, as well as key OEM requirements. Mobil Delvac Modern 15W-40 Full Protection may also be used in gasoline engines requiring the API SN specification and is suitable for use in applications requiring ISUZU and MAN specifications.

Developed in close collaboration with major OEMs, Mobil Delvac Modern 15W-40 Full Protection is recommended for use in a wide range of heavy duty applications and operating environments.

### Features and Benefits

Mobil Delvac Modern 15W-40 Súper Protección is formulated to deliver extended performance for up to 50% beyond OEM-recommended oil drain intervals<sup>1</sup>. This proprietary synthetic technology formulation delivers up to an average of 50 % more wear protection than required in API CK-4 engine tests , outstanding oxidation stability, and outstanding TBN retention.

Mobil Delvac Modern 15W-40 Súper Protección also provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high temperature deposits.

Features	Advantages and Potential Benefits
Outstanding oxidation stability	Extended ODI potential up to 1.5X the average OEM ODI recommendation <sup>1</sup> .
Resistance to corrosive and abrasive wear	Provides up to an average of 50 % more wear protection than required in API CK-4 engine tests.
Meets demanding specifications of key OEMs and latest API gasoline service category	One engine oil for mixed fleet operations
Excellent soot and viscosity control	Greater engine efficiency, long engine life and long oil life.
Excellent oil consumption control	Lower oil costs due to less make-up oil during operation
Outstanding TBN reserves	Corrosion protection and extended drain intervals for both new and old engines
Low temperature fluidity and pumpability	Formulated for smooth starting in cold weather
Component compatibility	Long gasket and seal life

Features	Advantages and Potential Benefits
Low ash formulation meeting API CK-4 and CJ-4 requirements	Long emissions aftertreatment life (DPF, DOC and SCR)
1 Based on US engine manufacturers' (OEM) average oil drain intervals (ODI) API CK-4 / API FA-4 recommendation. Results vary based on vehicle/engine condition, driving and environmental conditions. Consult OEM or ExxonMobil before implementing extended ODIs, especially if the equipment/vehicle is under warranty.	

### Applications

Mobil Delvac Modern 15W-40 Full Protection is formulated to deliver extended performance for up to 50% beyond OEM-recommended oil drain intervals<sup>1</sup>. This proprietary synthetic technology formulation delivers up to an average of 50 % more wear protection than required in API CK-4 engine tests, outstanding oxidation stability, and outstanding TBN retention.

Mobil Delvac Modern 15W-40 Full Protection also provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high temperature deposits.

### Specifications and Approvals

<b>This product has the following approvals:</b>
Detroit Detroit Fluids Specification 93K222
Detroit Fluids Specification 93K218
VOLVO VDS-4.5
MB-Approval 228.31
DQC II-18 LA
Mack EO-O Premium Plus
MACK EOS-4.5
VOLVO VDS-3
VOLVO VDS-4
RENAULT TRUCKS RLD-3
Mack EO-N Premium Plus 03
Cummins CES 20081
Cummins CES 20086

<b>This product is recommended for use in applications requiring:</b>
VOLVO VDS-2

**This product meets or exceeds the requirements of:**

API CH-4

API CI-4

API CI-4 PLUS

API CJ-4

API CK-4

API SM

API SN

ACEA E7

ACEA E9

API SL

Caterpillar ECF-3

API SP

JASO DH-2

**Properties and Specifications**

Property	
Grade	SAE 15W-40
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	109
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.8
Pour Point, °C, ASTM D97	-42
Density @ 15 C, g/ml, ASTM D1298	0.87
Viscosity Index, ASTM D2270	139
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Total Base Number, mgKOH/g, ASTM D4739	9.7
Ash, Sulfated, mass%, ASTM D874	0.9

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>


All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

Terpel Comercial del Perú S.R.L.  
Av. Jorge Basadre Grohmann 347,  
Interior 1005, San Isidro  
Lima, Perú  
24 Horas emergencia en salud      LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved