



Curve Grease 213

Mobil Grease , Peru

Railroad Rail Curve Grease

Product Description

Curve Grease 213, a lithium hydroxystearate grease, is designed to lubricate rail track curves, reducing friction and wheel wear. Curve Grease 213 contains molybdenum disulfide, a solid additive effective in reducing friction under boundary layer (metal-to-metal contact) conditions. Reducing friction decreases wheel wear and extends wheel life. Curve Grease 213 is also polymer enhanced, improving the ability to stay on the rail curve and resist water once applied.

Features and Benefits

Features	Advantages and Potential Benefits
Contains molybdenum disulfide	Contains 3 % molybdenum disulfide, reduces friction and wheel wear.
Polymer enhanced	Improves water resistance and ability to cling to rail curves.

Applications

Recommended by ExxonMobil for use in:

Rail curves where wheel/rail curve contact can lead to increased wheel wear.

Properties and Specifications

Property	
Grade	NLGI 1
Thickener Type	Lithium
Base Oil Viscosity of Greases @ 40 C, mm ² /s, AMS 1697	100
Color, Visual	Gray-Black
Dropping Point, °C, ASTM D2265	170
Penetration, 60X, 0.1 mm, ASTM D217	325

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2023

Terpel Comercial del Perú S.R.L.

Av. Jorge Basadre Grohmann 347,

Interior 1005, San Isidro

Lima, Perú

24 Horas emergencia en salud

LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com. ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved