



MOBIL SUPER GAS 10W-30 20W-50

Mobil Passenger Vehicle Lube , Peru

Premium Multigrade Passenger Vehicle Gas Engine Oils

Product Description

Mobil Super Gas 10W-30 and 20W-50 are premium quality mineral gas motor oils meeting the latest industry engine oil specifications. They are especially design for gas (VNG, LPG) and bi-fuel powered engines to provide a high level of performance and protection under most operating conditions.

Features and Benefits

Mobil Super Gas 10W-30 and 20W-50 are meticulously engineered for today's tougher engine specifications. It provides very good engine protection and helps prolong engine life.

- Enhanced thermal stability for high temperature conditions, which are common in gas powered engines
- Extended protection against engine wear and deposits formation
- Engine protection during start up
- Helps combat sludge

Applications

Mobil Super Gas 10W-30 and 20W-50 have been formulated to be suitable for use in nearly all vehicles. ExxonMobil particularly recommend Mobil Super Gas 10W-30 and 20W-50 for daily driving under normal and long haul conditions:

- Nearly all gas and bi-fuel powered engine technologies
- Passenger cars, SUV's, light trucks and vans
- Normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Specifications and Approvals

This product is recommended for use in applications requiring:	MOBIL SUPER GAS 10W-30	MOBIL SUPER GAS 20W-50
Fiat Chrysler Automotive MS-6395	X	
GM 6094M	X	

This product meets or exceeds the requirements of:	MOBIL SUPER GAS 10W-30	MOBIL SUPER GAS 20W-50
API SJ	X	X
API SL	X	X
API SM	X	
API SN	X	X
API SN PLUS	X	
API SN PLUS RESOURCE CONSERVING	X	

This product meets or exceeds the requirements of:	MOBIL SUPER GAS 10W-30	MOBIL SUPER GAS 20W-50
API SN Resource Conserving	X	

Properties and Specifications

Property	MOBIL SUPER GAS 10W-30	MOBIL SUPER GAS 20W-50
Grade	SAE 10W-30	SAE 20W-50
Density @ 15.6 C, g/ml, ASTM D4052	0.8665	
Flash Point, Cleveland Open Cup, °C, ASTM D92	228	230
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.7	20.1
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	73	154.3
Pour Point, °C, ASTM D97	-39	-30
Viscosity Index, ASTM D2270	137	141

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2021
Terpel Comercial del Perú S.R.L.
Av. Jorge Basadre Grohmann 347,
Interior 1005, San Isidro
Lima, Perú
24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTON

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved