



Mobil Super Gas 5W-30

Mobil Passenger Vehicle Lube , Peru

Synthetic Technology Gas Engine Oil

Product Description

Mobil Super Gas 5W-30 is an enhanced synthetic technology gas engine oil meeting the latest industry engine oil specifications. Especially designed for gas (VNG) and bi-fuel engines to provide an excellent level of protection and performance under the most demanding conditions.

Mobil Super Gas 5W-30 is industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super Gas 5W-30 contains synthetic technology formulation that provides excellent high temperature stability and protection, enhancing the performance of gas converted engines.

Features and Benefits

Mobil Super Gas 5W-30 is industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super Gas 5W-30 provides:

- Enhanced thermal stability, which allows the oil to not oxidized rapidly
- Excellent high temperature protection thanks to its high quality base oil formulation
- Provides superior engine protection during start up when compared to higher viscosity oils
- Its additive package provides excellent protection against engine wear and deposit formation.
- Thanks to its synthetic technology formulation provides improved fuel economy up to a 3%* by enabling the engine to work more efficiently

* Potential fuel economy improvement obtained by switching from higher viscosity oils to a lower viscosity grade. Actual savings are dependent upon vehicle/type, outside temperature, driving conditions and your current engine oil viscosity.

Applications

Mobil Super Gas 5W-30 is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle and conditions:

- Converted gas (VNG, LPG) and bi-fuel engines
- Latest gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Stop and Go City Driving
- Normal to severe operating conditions
- Turbo-Chargers
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:
Fiat Chrysler Automotive MS-6395

This product is recommended for use in applications requiring:

Ford WSS-M2C929-A

GM 6094M

This product meets or exceeds the requirements of:

API SJ

API SL

API SM

API SN

API SN Resource Conserving

Ford WSS-M2C946-A

Ford WSS-M2C946-B1

ILSAC GF-6A

API SP

API SP Resource Conserving

Properties and Specifications

Property	
Grade	SAE 5W-30
Viscosity Index, ASTM D2270	152
Density @ 15.6 C, g/ml, ASTM D4052	0.8581
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	63
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	16600
Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293	6040
Flash Point, Cleveland Open Cup, °C, ASTM D92	220

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

Terpel Comercial del Perú S.R.L.

Av. Jorge Basadre Grohmann 347,

Interior 1005, San Isidro

Lima, Perú

24 Horas emergencia en salud

LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com. ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved