



Mobil Super™ Multigrado 20W-50

Mobil Passenger Vehicle Lube , Peru

Premium quality multi-grade semi-synthetic oil for passenger vehicle engines

Product Description

Mobil Super™ Multigrado 20W-50 is a premium quality semi-synthetic motor oil that meets the industry's latest motor oil specifications. The product is designed to provide a high level of performance and protection under most operating conditions.

Features and Benefits

Engine protection during start-up

Long-term protection against engine wear and deposit formation

Helps fight sludge

Mobil Super Multigrado 20W-50 is meticulously designed to meet today's most stringent engine specifications. It provides very good engine protection and promotes long engine life.

Applications

Mobil Super Multigrado 20W-50 has been formulated for use in almost all vehicles. ExxonMobil recommends the oil especially for everyday driving under normal conditions.

- Almost all gasoline engine technologies
- Passenger vehicles, SUVs, light trucks and vans
- Normal operating conditions

Specifications and Approvals

This product meets or exceeds the requirements of:
API SP
API SN PLUS
API SN
API SM
API SL
API SJ

Properties and Specifications

Property	
Grade	SAE 20W-50
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	4.9
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	167
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	19.5
Flash Point, °C, ASTM D92	252
Ash, Sulfated, wt%, ASTM D874	0.7
Density @ 15 C, g/ml, ASTM D4052	0.874
Pour Point, °C, ASTM D97	-27

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2023
Terpel Comercial del Perú S.R.L.
Av. Jorge Basadre Grohmann 347,
Interior 1005, San Isidro
Lima, Perú
24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XT

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved