



MOBIL SUPER™ SEMISINTETICO 10W-30

Mobil Passenger Vehicle Lube , Peru

Premium Quality Synthetic Technology Oil for Passenger Vehicle Engines

Product Description

Mobil Super™ Semisintetico 10W-30 is a premium quality synthetic technology enhanced engine oil that meets the latest specifications of the industry's engine oil designed to provide an excellent level of protection and performance under the most demanding conditions.

Features and Benefits

Mobil Super™ Semisintetico 10W-30 is industry-proven so you can have confidence that you're getting the performance you want from your vehicle. It contains low-friction synthetic technology formulation that increases engine efficiency and provides improved fuel economy. Helps promote longer engine life.

Mobil Super™ Semisintetico 10W-30 provides:

- Thanks to its synthetic technology formulation, it provides improved fuel economy by up to 3%* by allowing the engine to run more efficiently
- Its additive package provides excellent protection against engine wear and deposit formation.
- Provides superior engine protection during start-up.
- Excellent protection at high temperatures thanks to its formulation with a high-quality base oil.

*Actual savings depend on the vehicle's engine type, outside temperature, driving conditions, and the viscosity of your current motor oil.

Applications

Mobil Super™ Semisintetico 10W-30 is formulated to give you confidence that your engine is receiving protection that goes far beyond what conventional oil can provide. We recommend it in particular for the following vehicle types and conditions:

- The latest gasoline engine technologies
- Passenger vehicles, SUVs, light trucks and vans
- Driving in the city with many stops
- Normal to severe operating conditions
- Turbochargers
- High-performance engines

Always check your owner's manual to check the recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SP
ILSAC GF-6A

Properties and Specifications

Property	
Grade	SAE 10W-30
Viscosity Index, ASTM D2270	146
Pour Point, °C, ASTM D97	-36
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Density @ 15.6 C, g/ml, ASTM D4052	0.8612
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.3
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	65
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2023
Terpel Comercial del Perú S.R.L.
Av. Jorge Basadre Grohmann 347,
Interior 1005, San Isidro
Lima, Perú
24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved