



**Mobil 1™ FS X2 5W-50**  
Mobil Passenger Vehicle Lube , Peru  
Advanced Full Synthetic Motor Oil

**Product Description**

Mobil 1™ FS X2 5W-50 European Car Formula is an advanced full synthetic motor oil engineered for the latest gasoline and diesel (without Diesel Particulate Filtration) engine technology delivering excellent all-round performance. It provides exceptional cleaning power, wear protection and overall performance. Mobil 1 5W-50 keeps your engine running like new and protects for 10,000 miles\*

\*Protects for up to 10,000 miles or 1 year, whichever comes first. To learn more about the Mobil 1 Limited Warranty, visit [Mobil.US](https://www.mobil.us).

**Features and Benefits**

- Mobil 1™ FS X2 5W-50 is made with a proprietary blend of high performance synthetic basestocks fortified with a precisely balanced component system. Key features and potential benefits include:
- Meets or exceeds the latest applicable OEM and industry specifications.
  - Provides excellent overall performance.
  - Has excellent low temperature capabilities for rapid engine protection at start-up.
  - Delivers fast protection for reduced engine wear and deposits
  - Provides exceptional cleaning power for your engine.

**Applications**

- Mobil 1™ FS X2 5W-50 is recommended by ExxonMobil for all types of vehicles, including high-performance turbo-charged, supercharged gasoline and certain multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks.
- Mobil 1™ FS X2 5W-50 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Always check your owner's manual for the manufacturer's recommended oil viscosity grade and specifications for your particular vehicle.

**Specifications and Approvals**

|   |
|---|
| <b>This product has the following approvals:</b>                      |
| MB-Approval 229.3   |
| <b>This product is recommended for use in applications requiring:</b> |
| API CF  |
| FIAT 9.55535-M2   |
| <b>This product meets or exceeds the requirements of:</b>             |
| API SJ  |
| API SL  |

**This product meets or exceeds the requirements of:**

API SM

API SN

API SN PLUS

API SP

ACEA A3/B4

LEXUS LFA Service Fill

**Properties and Specifications**

| Property  |           |
|---|-----------|
| Grade   | SAE 5W-50 |
| Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684  | 31600     |
| Viscosity Index, ASTM D2270   | 185       |
| Density @ 15.6 C, g/ml, ASTM D4052                                    | 0.8406    |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445            | 18.6      |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683 | 4.3       |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445             | 112.5     |
| Flash Point, Cleveland Open Cup, °C, ASTM D92                         | 225       |
| Ash, Sulfated, mass%, ASTM D874                                       | 0.98      |
| Pour Point, °C, ASTM D97  | -37       |
| Total Base Number, mgKOH/g, ASTM D2896                                | 12.5      |

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2023

Terpel Comercial del Perú S.R.L.

Av. Jorge Basadre Grohmann 347,

Interior 1005, San Isidro

Lima, Perú

24 Horas emergencia en salud

LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved