



## Mobil Special™ Alto Kilometraje 25W-60

Mobil Passenger Vehicle Lube , Peru

Automotive Engine Oil

### Product Description

Mobil Special Alto Kilometraje is a unique formula that is especially designed for engines with over 100,000 kilometers. The 25W-60 viscosity provides a thick oil film that helps protect gasoline engines that operate in severe service such as high temperatures and in city traffic where stop-and-go driving is common. Mobil Special Alto Kilometraje is formulated from quality base stocks combined with performance additives, which help protect against the formation of sludge and corrosion.

### Features and Benefits

Mobil Special Alto Kilometraje:

- Helps to reduce engine wear and corrosion in higher mileage vehicles
- Protects under a wide variety of operating conditions, especially high temperatures
- Helps reduce oil leakage due to the thick oil film
- Reduce oil consumption

### Applications

Mobil Special Alto Kilometraje is recommended by ExxonMobil for higher mileage vehicles including turbo charged, super charged, fuel injected, multi-valve and normally aspirated engines. Before using Mobil Special Alto Kilometraje, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

### Specifications and Approvals

This product meets or exceeds the requirements of:
API SJ
API SL

### Properties and Specifications

Property	
Grade	SAE 25W-60
Pour Point, °C, ASTM D97	-21
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	264.1

Property	
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	24.5
Total Base Number, mgKOH/g, ASTM D2896	7.2
Viscosity Index, ASTM D2270	118
Density @ 15 C, g/ml, ASTM D4052	0.898
Flash Point, Cleveland Open Cup, °C, ASTM D92	246

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020

Terpel Comercial del Perú S.R.L.

Av. Jorge Basadre Grohmann 347,

Interior 1005, San Isidro

Lima, Perú

24 Horas emergencia en salud      LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved