



## Mobil Super Moto™ Gas 4T 20W-50

Mobil Passenger Vehicle Lube , Peru

High Performance Four-Stroke Motorcycle and Trike Motorcycle Gas and Bi-Fuels Engine Oil

### Product Description

Mobil Super Moto™ Gas 4T 20W-50 is a high performance conventional four-stroke motorcycle gas engine oil primarily intended for general use in trike motorcycles. It is formulated to provide enhanced protection for the high demands posed on trike motorcycles. Mobil Super Gas 4T 20W-50 is especially designed for gas (VNG, LPG) and bi-fuel powered motorcycle engines to provide an excellent level of protection and performance under the most demanding conditions.

### Features and Benefits

Mobil Super Moto Gas 4T 20W-50 combines highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection. Key features and benefits include:

- Excellent features to protect trike motorcycles engines under severe conditions
- Enhanced thermal stability against high temperatures generated in gas powered engines
- Good protection against wear that helps increase engine life
- Thermal and oxidation stability, which allows the oil to not oxidized rapidly and helps to keep engine cleanliness for smoother operation
- Excellent features to protect engine, clutch and transmission
- Good corrosion protection which helps to protect critical engine components

Features	Advantages and Potential Benefits
Good wear protection	Helps extend engine life
Thermal and oxidation stability	Helps keep engines clean to provide smoother operation
Good corrosion protection	Protects critical engine components

### Applications

Mobil Super Moto Gas 4T 20W-50 is a high performance mineral gas motor oil that has been especially designed to provide enhanced protection for the high demands of trike motorcycles.

### Specifications and Approvals

This product meets or exceeds the requirements of:
API SL
JASO MA2
JASO MA

### Properties and Specifications

Property	
Grade	SAE 20W-50
Ash, Sulfated, mass%, ASTM D874	0.79
Pour Point, °C, ASTM D97	-27
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	169.2
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	19.3
Flash Point, °C, ASTM D92	237
Density @ 15.6 C, g/ml, ASTM D4052	0.8847

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020

Terpel Comercial del Perú S.R.L.

Av. Camino Real 456,

Torre Real Piso 14 San Isidro

Lima Perú

24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil Esso XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved